




DIMENSIONS (in inches)

CASE STYLE	A	B	C	D	E
X	4-1/4	4-3/4	3-1/2	2	1-1/2
Y	2-3/4	3	2-3/8	1-13/16	1-3/8
Z	6	6-7/16	5-7/16	2-1/4	1-5/8
MM	5-3/4	6-5/16	5-1/16	1-7/8	1-3/8



Self Start-Canned Type Preheat (Starter Built In)

Lamp Data		Volts	Catalog Number	ANSI	Certification & Approval	Dimension Pg. & Illus.	Wiring Diagram (No.)	Shipping Data	
Description	Watts			Lamp Current (Amps)				Weight Per Unit (pounds)	Standard Pack

ONE LAMP and TWO LAMP / NORMAL POWER FACTOR									
F6T5	6	120	AS468 AS468ST	.170	UL-CSA UL	22 Y	11	.9	36
F8T5	8	120	AS468 AS468ST	.180	UL-CSA UL	22 Y	11	.9	36
F14T8	14	120	AS452 AS452ST	.380	UL-CSA UL	22 Y	11	.9	36
F15T8 or F15T12	15	120	AS452 AS452ST	.300	UL-CSA UL	22 Y	11	.9	36
F20T12	20	120	AS452 AS452ST	.380	UL-CSA UL	22 Y	11	.9	36
FC8T9 or FC8T9	15 or 22	120	AS452 AS452WC AS452WCST AS452ST	.380	UL-CSA UL UL UL	22 Y	11 12 12 11	.9	36
F25T12	25 25 (2)25	120	AS125 AS125ST AS225	.500 .500 1.000	UL-CSA UL UL	22 X 22 X 22 Z	11	1.6 1.6 2.50	24
F30T8	30	120	AS340 AS340ST	.650	UL-CSA UL-CSA	22 MM	11	1.75	30
FC12T9	32	120	AS340 AS340ST	.650	UL-CSA UL	22 MM	11	1.75	30
F12" T10BL550	35 (2)35	120	AS135 AS235	.550 1.100	UL-CSA UL	22 X 22 Z	11	1.7 2.50	24

WC = with connector
ST = starter built in tube