



# Reflector Infrared BR40,PAR38

### 125BR40/1/TG 120V 4/1

Philips Family of Specialty Incandescents provide the perfect light for dramatic accents and display lighting as well as general lighting in a variety of applications. Philips Infrared lamps are suited for heating and drying in industrial and commercial aplications. These incandescent, gas-filled infrared heat lamps come up to full temperature almost immediately, eliminating costly warm-up time. Highly efficient heat generators that produce a minimum of light rays and a high amount of infrared radiation. The BR40 lamp provides a built-in reflector for radiant energy control.

#### **Product data**

General Information			
Cap-Base	E26 [ Single Contact Medium Screw]		
Operating Position	UNIVERSAL [ Any or Universal (U)]		
Main Application	Infrared		
Gas Filling	Gas		
Footnote Incandescent 1	Average laboratory life in excess of 5000 hours. In-service life		
	depends upon service conditions. (27)		
Footnote Incandescent 2	Do not allow hot bulb to come in contact with liquid or metal		
	parts of the fixture, as glass may shatter. Do not use outdoors.		
	Do not operate in close proximity to flammable materials or		
	those adversely affected by heat or drying. Operate only in heat		
	resistant sockets. (87)		
Footnote Incandescent 3	CAUTION: Do not operate in close proximity to flammable		
	materials or those adversely affected by heat or drying. Operate		
	only in heat resistant sockets. WARNING: Use carefully. May		
	cause serious burns. Do not use over insensitive skin areas or in		
	the presence of poor circulation. The unattended use of infrared		

	heat by children or incapacitated persons may be dangerous.—		
	Lamp should not be placed closer that 18" to the surgace being		
	irritated.—Do not use dor therapeutic or topical applications		
	unless recommended by a physician.—For food warming, use		
	only lamps with heat resisting glass. (89)		
Footnote Incandescent 4	Circle E-The encircled E means this bulb meets Federal		
	minimum efficiency standards.		
Light Technical			
Beam Description	Spot		
Operating and Electrical			
Power (Rated) (Nom)	125 W		
Voltage (Nom)	120 V		

Datasheet, 2016, October 10 data subject to change

# Reflector Infrared BR40,PAR38

Mechanical and Housing	J
Bulb Finish	Clear
Cap-Base Information	Aluminium Cap
Filament Shape	C-9 [ Pendant]
Product Data	
Order product name	125BR40/1/TG 120V 4/1
EAN/UPC - Product	046677159306
Order code	925254936309

Numerator - Quantity Per	1
Pack	
Numerator - Packs per outer	4
box	
Material Nr. (12NC)	925254936309
Net Weight (Piece)	0.001 kg

## Dimensional drawing

Product	P	ro	d	uc	ŧ
---------	---	----	---	----	---

125BR40/1/TG 120V 4/1

125W E26 120V BR40 SP CL

