

PAR30L LED Single Optic lamp with AirFlux Technology

12PAR30L/F25 4000 DIM AF SO 6/1

Philips PAR30L LED Retail Optic lamp with AirFlux Technology improves shopping experience with superior lighting aesthetics and optimal thermal efficiency in a sleek, lightweight design.

Product data

• General Characteristics

Cap-Base PAR30L Bulb Rated Avg. Life 50000 hr (Hours)

• Light Technical Characteristics

Color Code WH Color Designation White Beam Angle 25 D

Beam Description 25D [Medium beam]

4000 K Correlated Color

Temperature

950 Lm Approximate Lumens Approx. MBCP 5500 cd 82 79.17 Lm/W Luminous Efficacy

Lamp

4000 K [CCT 4000K] Color Temp. (Kelvin)

Rated Luminous Flux 950 Lm

• Electrical Characteristics

12 W Wattage Wattage Technical 12 W 120 V Voltage Line Frequency 60 Hz 0.9 -Power Factor Lamp Current mA 113 mA

Dimmable Yes 75 W Wattage Equivalent 0.5 s Starting Time

• Environmental characteristics

Energy consumption 12 kWh kWh/1000h

• Measuring Conditions

20000X Switching cycle

• Product Dimensions

Overall Length C 116 mm Diameter D 92 mm

• Product Data

Product number Full product name 12PAR30L/F25 4000 DIM AF SO 6/1 Short product name 12PAR30L/F25 4000 DIM AF RO 6/1

Pieces per Sku eop_pck_cfg Skus/Case

46677430146 Bar code on pack 50046677430141 Bar code on case Logistics code(s) 929000251504 0.240 kg eop_net_weight_pp






PAR30L LED Single Optic lamp with AirFlux Technology

Warnings and Safety

- Suitable for use in damp locations.
- Not for use in totally enclosed luminaires.

• Before replacing, turn off power and let lamp cool to avoid electrical shock or burn.

Dimensional drawing



12PAR30L/F25 4000 DIM AF SO 6/1

Product	C (Norm)	C1 (Max)	D (Norm)	D1 (Norm)
LED 12-75W E26 4000K 120V PAR30L 25D DIM	116	-	92	-



E26



© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.