

Project Name:	Type:
Part Number:	Date:

VALUE SELECT HIGH CRI PAR FAMILY

FEATURES

- Suitable to replace 50W, 75W, 120W halogen
- Smooth dimming with most forward and reverse phase dimmers*
- Suitable for use in wet locations
- CRI 90+ produces rich and vibrant colors
- Compact size 1:1 halogen form factor
- Narrow & flood beam angles
- Suitable for use in totally enclosed fixtures
- Fixture operating temperature: -4°F to 95°F (-20°C to 35°C)
- Lamp ambient temperature: -4°F to 113°F (-20°C to 45°C)
- Rated Lifetime (L70): 25,000hrs
- 3 years limited warranty**



041124




SPECIFICATIONS

Product	Model	Equiv.	CCT	Wattage (W)	Lumens (LM)	Efficacy (LPW)	Power Factor	Input Voltage	CRI	Beam Angle	CBP (cd)	Dim.	Fixture Rating	ES / T20
37068	5.5PAR20DIM/927FL40	50W	2700K	5.5	520	95	0.9	120V	90	40°	595	Yes	Enclosed	✓ / ✓
37069	5.5PAR20DIM/930FL40	50W	3000K	5.5	525	95	0.9	120V	90	40°	600	Yes	Enclosed	✓ / ✓
37070	8PAR30DIM/930FL40	75W	3000K	8	800	100	0.7	120V	90	40°	1,315	Yes	Enclosed	✓ / ✓
37071	8PAR30DIM/940FL40	75W	4000K	8	800	100	0.7	120V	90	40°	1,315	Yes	Enclosed	✓ / ✓
37072	8PAR30SNDIM/930NF25	75W	3000K	8	800	100	0.7	120V	90	25°	2,910	Yes	Enclosed	✓ / ✓
37074	13PAR38DIM/930FL40	120W	3000K	13	1,250	96	0.7	120V	90	40°	2,235	Yes	Enclosed	✓ / ✓
37075	13PAR38DIM/940FL40	120W	4000K	13	1,250	96	0.7	120V	90	40°	2,235	Yes	Enclosed	✓ / ✓

* This lamp might not be compatible with all dimmers. Please visit www.greencreative.com for compatibility information.

** Please visit www.greencreative.com for Limited Warranty terms.


DIMENSIONS & WEIGHT




Model	Base	MOL	Dia.	Weight
5.5PAR20DIM/xxxxxxx	E26	3-3/16"	2-1/2"	0.12lb

VALUE SELECT HIGH CRI PAR FAMILY


DIMENSIONS & WEIGHT



Model	Base	MOL	Dia.	Weight
8PAR30DIM/xxxxyyy	E26	4-5/16"	3-5/8"	0.20lb




Model	Base	MOL	Dia.	Weight
8PAR30SNDIM/xxxxyyy	E26	3-5/16"	3-5/8"	0.23lb




Model	Base	MOL	Dia.	Weight
13PAR38DIM/xxxxyyy	E26	5-1/16"	4-3/4"	0.37lb

ILLUMINANCE & CANDELA DISTRIBUTION

5.5PAR20DIM/927FL40




Diameter	Footcandles
2.2	203
4.4	51
6.6	23
8.7	13
10.9	8




Degree	Candela
0	979
5	910
15	561
25	254
35	114
45	53

5.5PAR20DIM930FL40



Diameter	Footcandles
2.2	196
4.4	49
6.6	22
8.7	13
10.9	8




Degree	Candela
0	948
5	890
15	590
25	289
35	134
45	64


VALUE SELECT HIGH CRI PAR FAMILY

ILLUMINANCE & CANDELA DISTRIBUTION

8PAR30DIM/930FL40




Diameter	Footcandles
2.2	353
4.4	88
6.6	39
8.7	23
10.9	14




Degree	Candela
0	1,657
5	1,541
15	1,041
25	533
35	217
45	71

8PAR30DIM/940FL40




Diameter	Footcandles
2.2	385
4.4	96
6.6	43
8.7	25
10.9	16




Degree	Candela
0	1,865
5	1,745
15	1,129
25	571
35	215
45	68

8PAR30SNDIM/930NF25




Diameter	Footcandles
1.1	2,771
2.2	693
3.2	327
4.3	181
5.4	115




Degree	Candela
0	3,282
5	2,695
15	1,028
25	363
35	156
45	67

8PAR30SNDIM930FL40



Diameter	Footcandles
2.2	347
4.4	87
6.6	39
8.7	22
10.9	14




Degree	Candela
0	1,678
5	1,561
15	1,034
25	535
35	210
45	67


VALUE SELECT HIGH CRI PAR FAMILY

ILLUMINANCE & CANDELA DISTRIBUTION

13PAR38DIM/930FL40




Diameter	Footcandles
2.2	576
4.4	144
6.6	64
8.7	37
10.9	23




Degree	Candela
0	2,786
5	2,591
15	1,664
25	812
35	327
45	89

13PAR38DIM/940FL40



Diameter	Footcandles
2.2	548
4.4	137
6.6	61
8.7	35
10.9	22



Degree	Candela
0	2,653
5	2,557
15	1,650
25	834
35	344
45	114

ORDERING INFORMATION

Model	Master Carton			Shipping Carton		
	Case Qty	Case Dimensions (LxWxH)	Case Weight	Case Qty	Case Dimensions (LxWxH)	Case Weight
5.5PAR20DIM/xxxxyyy	6PCS	8"x 5-1/2" x 3-7/8"	1.15 lb	24PCS	11-1/2"x 8-5/8" x 8-15/16"	5.29 lb
8PAR30DIM/xxxxyyy	6PCS	11-13/16" x 7-7/8" x 5"	2.03 lb	24PCS	16-9/16" x 12-3/8" x 12"	8.82 lb
8PAR30SNDIM/930NF25	6PCS	11-13/16" x 7-7/8" x 4-3/16"	2.20 lb	24PCS	16-9/16" x 12-3/8" x 9-13/16"	9.48 lb
8PAR30SNDIM/930FL40	6PCS	11-13/16" x 7-7/8" x 4-3/16"	1.92 lb	24PCS	16-9/16" x 12-3/8" x 9-13/16"	8.38 lb
13PAR38DIM/xxxxyyy	6PCS	14-7/8" x 10" x 6-5/16"	3.66 lb	24PCS	20-1/2" x 15-3/8" x 13-3/4"	16.53 lb

Where xxx means 824-965 which indicates CRI and color temperature
Where yyy means beam angle

CERTIFICATION INFORMATION

Product	Model	ES ID#
37068	5.5PAR20DIM/927FL40	2401136
37069	5.5PAR20DIM/930FL40	2401137
37070	8PAR30DIM/930FL40	2401138
37071	8PAR30DIM/940FL40	2401139
37072	8PAR30SNDIM/930NF25	2401140
37073	8PAR30SNDIM/930FL40	2401141
37074	13PAR38DIM/930FL40	2401142
37075	13PAR38DIM/940FL40	2401143
37069	5.5PAR20DIM/930FL40	2401137
37073	8PAR30SNDIM/930FL40	2401141
37074	13PAR38DIM/930FL40	2401142

Note: All rights reserved. All sizes and specifications are subject to change at any time without notice.