



T8

13T8-6U/MAS/24-835/IF20/P/DIM 10/1

Our TLEDs are available in InstantFit (Type A / Type C) or MainsFit (Ballast bypass / Type B) versions. The InstantFit lamps work on a broad variety of ballasts and LED drivers. Only InstantFit has over 15,000 lamp & ballast combinations delivering even light output, energy savings and a long lifetime. Our MainsFit products feature a double-ended design, simplifying installation while a proprietary safety circuit minimizes a shock risk. Lamp sizes range from 2-foot to 8-foot and U-bend with a variety of lumen outputs.

Product data


General Information		Starting Time (Nom)		0.5 s
Base	G13 [Medium Bi-Pin Fluorescent]	Warm Up Time to 60% Light (Nom)		0.5 s
EU RoHS compliant	Yes	UL Type		Type A - works on ballast
Nominal Lifetime (Nom)	70000 h	Power Factor (Nom)		0.9
Switching Cycle	50000X	Voltage (Nom)		120-277, 347 V
Light Technical		Temperature		
Color Code	835 [CCT of 3500K]	T-Ambient (Max)		45 °C
Beam Angle (Nom)	180 °	T-Ambient (Min)		-20 °C
Initial lumen (Nom)	2000 lm	T-Storage (Max)		65 °C
Color Designation	White (WH)	T-Storage (Min)		-40 °C
Correlated Color Temperature (Nom)	3500 K	T-Case Maximum (Nom)		50 °C
Luminous Efficacy (rated) (Nom)	153.00 lm/W	Controls and Dimming		
Color Consistency	<6	Dimmable		Yes
Color Rendering Index (Nom)	80	Mechanical and Housing		
LLMF At End Of Nominal Lifetime (Nom)	70 %	Bulb Material		Plastic
Operating and Electrical		Product Length		24 in
Input Frequency	20K to 120K Hz			
Power (Rated) (Nom)	13 W			

Bulb Shape	Tube, double-ended
Approval and Application	
Energy Efficiency Label (EEL)	Not applicable
Energy Saving Product	Yes
Approbation Marks	RoHS compliance UL certificate DLC compliance
Energy Consumption kWh/1000 h	- kWh
Energy Certifications	DLC Standard

Product Data	
Order product name	13T8-6U/MAS/24-835/IF20/P/DIM 10/1

EAN/UPC - Product	046677541866
Order code	541862
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001987504
Net Weight (Piece)	0.270 kg
Model Number	9290019875


Dimensional drawing




TLED IF MasterClass U bent 2000lm 3500K

Product	D1	D2	A1	A2	A3
13T8-6U/MAS/24-835/ IF20/P/DIM 10/1	25.7 mm	28 mm	152 mm	570 mm	27.8 mm

Photometric data




G13 3000K 2000lm



G13 3500K 2000lm



Photometric data




Calicut Potamoceros 4.5	Polys Lighting B.V.	Page: 1/1
-------------------------	---------------------	-----------

G13 3500K 2000lm


Lifetime



G13 3000K 2000lm




G13 4000K



G13 4000K

G13 4000K

Lifetime



G13 4000K

