

The Philips Family of Silicone Coated Rough Service bulbs are the perfect choice in areas where there is concern if a bulb drops or shatters. Since Silicone Coated Rough Service bulbs resist breakage or shattering, they are perfect for food serving areas, as well as, standard, industrial rough surface, appliance and sign use.

Product data

• General Characteristics

| | |
|--------------------|--------------------------------------|
| Base | Medium [Single Contact Medium Screw] |
| Base Information | Aluminum [Aluminum Base] |
| Bulb | A21 |
| Bulb Finish | Frost Silicone |
| Filament Shape | RC-9 [Reinforced Construction C-9] |
| Operating Position | Universal [Any or Universal (U)] |
| Main Application | Rough Service |
| Atmosphere | Gas |

• Electrical Characteristics

| | |
|---------|-----------|
| Watts | 150 W |
| Voltage | 120-130 V |

• Product Dimensions

| | |
|------------------------------|----------------|
| Max Overall Length (MOL) - C | 5.313 (max) in |
| Diameter D | 2.625 in |

• Footnotes

| | |
|------------------------|--|
| Footnotes Incandescent | 66 [Silicone Coating reduces lumen output from Standard Values less than 3%. (66)] |
|------------------------|--|

• Product Data

| | |
|--------------------|-----------------------------------|
| Product number | 149690 |
| Full product name | Sil Ctd 150W Med 120-130V A21 2WR |
| Short product name | Sil Ctd 150W Med 120-130V A21 2WR |
| Pieces per Sku | 1 |
| eop_pck_cfg | 60 |
| Skus/Case | 60 |
| Bar code on pack | 46677279837 |
| Bar code on case | 50046677149692 |
| Logistics code(s) | 925240634305 |
| eop_net_weight_pp | 0.001 kg |