


PL DIR LINE

PL BYP / HYBM LINE



- Plug & Play installation (electronic ballasts only)
- Compatible with G24q & GX24q sockets
- Patented design
- Compatible with select 0-10V dimmable ballasts and controls
- Ballast Adaptive Technology allows one LED lamp to be powered by a range of fluorescent ballasts instead of restricting to one wattage rating

High Flexibility - Ballast Adaptive Technology		
Ballast Type	Lumens	Bare Lamp
13W	590	5W
18W	820	6W
26W	1020	9.5W
PL V 9.5W DIR		

SPECIFICATIONS												
Product	Model	CCT	Lumens	CRI (typ.)	LPW	Dim	Equiv.	Beam Angle	Life (hrs)	Voltage	Encl.	DLC
28370	6PLV/827/DIR/R	2700K	600	82	100	Yes	13-18W	120°	50,000	120-277V	No	N.A.
28371	6PLV/830/DIR/R	3000K	620	82	103	Yes	13-18W	120°	50,000	120-277V	No	N.A.
28372	6PLV/835/DIR/R	3500K	620	82	103	Yes	13-18W	120°	50,000	120-277V	No	N.A.
28373	6PLV/840/DIR/R	4000K	640	82	107	Yes	13-18W	120°	50,000	120-277V	No	N.A.
28374	9.5PLV/827/DIR/R	2700K	950	82	100	Yes	26W	120°	50,000	120-277V	No	✓
28375	9.5PLV/830/DIR/RC	3000K	1,000	82	105	Yes	26W	120°	50,000	120-277V	No	✓
28376	9.5PLV/835/DIR/RC	3500K	1,000	82	105	Yes	26W	120°	50,000	120-277V	No	✓
28377	9.5PLV/840/DIR/RC	4000K	1,020	82	107	Yes	26W	120°	50,000	120-277V	No	✓
57918	11PLV/930/DIR/R	3000K	920	92	84	Yes	26W	120°	50,000	120-277V	No	N.A.
98248	17PLV/830/DIR	3000K	1,900	82	112	Yes	42W	120°	50,000	120-277V	No	✓
98249	17PLV/835/DIR	3500K	1,950	82	115	Yes	42W	120°	50,000	120-277V	No	✓
98250	17PLV/840/DIR	4000K	2,000	82	118	Yes	42W	120°	50,000	120-277V	No	✓



- HYBrid installation - DIRection or BYPass
- Compatible with magnetic ballasts - DIRection installation
- Built-in universal voltage driver - BYPass installation
- 310° rotatable base allows light to be directed as needed

SPECIFICATIONS											
Product	Model	CCT	Lumens	CRI (typ.)	LPW	Dim	Equiv.	Beam Angle	Life (hrs)	Voltage	Encl.
36086	5.5PLH/827/HYBM	2700K	550	82	100	No	13-18W	110°	50,000	120-277V	No
34856	5.5PLH/830/HYBM	3000K	550	82	100	No	13-18W	110°	50,000	120-277V	No
36642	5.5PLH/835/HYBM/R	3500K	600	82	109	No	13-18W	110°	50,000	120-277V	No
36643	5.5PLH/840/HYBM/R	4000K	620	82	113	No	13-18W	110°	50,000	120-277V	No
98399	8PLH/827/HYBM	2700K	870	82	109	No	26W	110°	50,000	120-277V	No
98400	8PLH/830/HYBM	3000K	920	82	115	No	26W	110°	50,000	120-277V	No
98401	8PLH/835/HYBM	3500K	920	82	115	No	26W	110°	50,000	120-277V	No
98402	8PLH/840/HYBM	4000K	950	82	119	No	26W	110°	50,000	120-277V	No
36638	15.5PLH/827/BYP/R	2700K	1,750	82	113	No	42W	110°	50,000	120-277V	No
36639	15.5PLH/830/BYP/R	3000K	1,850	82	119	No	42W	110°	50,000	120-277V	No
36640	15.5PLH/835/BYP/R	3500K	1,950	82	126	No	42W	110°	50,000	120-277V	No
36641	15.5PLH/840/BYP/R	4000K	2,000	82	129	No	42W	110°	50,000	120-277V	No

Note: PL H 15.5W BYP operates on line voltage only and is not compatible with magnetic ballasts