Presented By: Candela Corporation

Contact Phone: 800-922-9226


Contact E-mail: sales@candelacorp.com



GE Lighting

12859 - 1962BG

GE Quartzline® T3 - Low Voltage







CAUTIONS & WARNINGS

Caution

- Risk of Burn
- Allow lamp/fixture to cool before handling.

Warning

- Lamp emits UV radiation which may cause eye/skin irritation.
- Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in fixture rated for this product.
- $\bullet \ \mathsf{Pressurized} \ \mathsf{lamp}\text{--unexpected rupture may cause injury, fire, or property damage}$
- Dispose of lamp in a closed container.
- Do not exceed rated voltage.
- Do not touch glass with bare hands.
- Do not turn on lamp until fully installed
- Do not use lamp if outer glass is scratched or broken.
- Keep children away.
- Use eye protection when handling lamp.
- Use protective screen when handling.

Customer Name: Project Name: Fixture Type:

GENERAL CHARACTERISTICS

Lamp Type Miniature - T & TL Shape

Bulb T3

Base Wire Terminals

Filament C-6
Rated Life (NOM) 50.0 h
Bulb Material Quartz
Atmosphere Gas-filled
Primary Application Low Voltage

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 1382.0 Nominal Initial Lumens per Watt 22.29032

(NOM)

Mean Spherical Candlepower

(MSCP) (NOM)

110.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 62.0 Voltage (NOM) 8.5

DIMENSIONS

Maximum Overall Length (MOL) (NOM)

Bulb Diameter (DIA) (NOM) 0.375 in(9.5 mm)
Light Center Length (LCL) 0.285 in(7.2 mm)
(NOM)

PRODUCT INFORMATION

Product Code 12859
Description 1962BG
ANSI Code 1962BG
Standard Package Case

Standard Package GTIN 10043168128596

Standard Package Quantity 10
Sales Unit Bulk
No Of Items Per Sales Unit 1
No Of Items Per Standard 10

Package

UPC 043168128599