Presented By: Candela Corporation

Contact Phone: 800-922-9226

Contact E-mail: sales@candelacorp.com


Customer Name: Project Name: Fixture Type:



GE Lighting

41938 - 1970X

GE Quartzline® T3 - Aircraft; Low Voltage







CAUTIONS & WARNINGS

Caution

- Risk of Burn
- Allow lamp/fixture to cool before handling.

Warning

- Lamp emits UV radiation which may cause eye/skin irritation.
- Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Dispose of lamp in a closed container.
- Do not exceed rated voltage.
- Do not touch glass with bare hands.
- Do not turn on lamp until fully installed.
- Do not use lamp if outer glass is scratched or broken.
- Keep children away.
- Use eye protection when handling lamp.
- Use protective screen when handling.

NOTES

· Filament supported.

GENERAL CHARACTERISTICS

Lamp Type Miniature - T & TL Shape

Bulb T3

Base Special Sleeve
Filament CC-8
Rated Life (NOM) 1000.0 h
Atmosphere Gas-filled

Primary Application Aircraft; Low Voltage

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 1759.0 Nominal Initial Lumens per Watt 17.59

(NOM)

Mean Spherical Candlepower

(MSCP) (NOM)

140.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 100.0 Voltage (NOM) 28.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM)

Bulb Diameter (DIA) (NOM) 0.375 in(9.5 mm)

PRODUCT INFORMATION

Product Code 41938
Description 1970X
ANSI Code 1970X
Standard Package Case

Standard Package GTIN 20043168419387

Standard Package Quantity 10
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 10

Package

UPC 043168419383