Presented By: Candela Corporation


Contact Phone: 800-922-9226

Contact E-mail: sales@candelacorp.com



26698 - 2059X UNIT

GE T2.5 (T2 1/2) - Aircraft; Low Voltage







CAUTIONS & WARNINGS

Caution

- Risk of Burn
- Allow lamp/fixture to cool before handling.

Warning

- Lamp emits UV radiation which may cause eye/skin irritation.
- Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in fixture rated for this product.
- $\bullet \ \mathsf{Pressurized} \ \mathsf{lamp}\text{--unexpected rupture may cause injury, fire, or property damage}$
- Dispose of lamp in a closed container.
- Do not exceed rated voltage.
- Do not touch glass with bare hands.
- Do not turn on lamp until fully installed
- Do not use lamp if outer glass is scratched or broken.
- Keep children away.
- Use eye protection when handling lamp.
- Use protective screen when handling.

Customer Name: Project Name: Fixture Type:

GENERAL CHARACTERISTICS

Lamp Type Miniature - T & TL Shape

Bulb T2.5 (T2 1/2)

Base Miniature Bayonet (Ba9s)

Filament C-8
Rated Life (NOM) 4000.0 h
Atmosphere Gas-filled

Primary Application Aircraft; Low Voltage

PHOTOMETRIC CHARACTERISTICS

Mean Spherical Candlepower 8.0

(MSCP) (NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 10.0 Voltage (NOM) 12.0

DIMENSIONS

Maximum Overall Length 1.300 in(33.0 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 0.312 in(7.9 mm) Light Center Length (LCL) 0.590 in(15.0 mm)

(NOM)

PRODUCT INFORMATION

Product Code 26698
Description 2059X UNIT
ANSI Code 2059X
Standard Package Case

Standard Package GTIN 10043168266984

Standard Package Quantity 10
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 10

Package

UPC 043168266987