Project Name Location Prepared By



SATCO S29911

25T5/LED/46-850/DR

Notes

| General | |
|------------------------|------------------|
| Watts | 25 |
| Fluorescent Equivalent | 54 |
| Ballast Type | Туре А |
| Shape | T5 |
| Base | Miniature Bi Pin |
| ANSI Base | G5 |
| Nominal Length | 48 |
| Finish | Gloss |
| CCT (Kelvin) | 5000 |
| Temperature | Natural Light |
| CRI | 82 |
| Lumens | 3500 |
| Beam Spread | 185 |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Technology | LED |

| Electrical | |
|-------------------------|---|
| Ballasting Requirements | Ballast required |
| Power Factor | 0.9 |
| Operating Temperature | -20C (-4F) to a maximum of +45C (+113F) |

| Physical | | |
|----------|------|--|
| MOL | 48 | |
| MOD | 0.63 | |

| Additional Information | |
|------------------------|---------------------------------|
| Includes | Integrated thermal fuse at pins |
| Warranty | 5 Year Limited |

| Compliance | |
|----------------|-------------------------------|
| Safety Listing | cULus - Damp |
| Energy Star | No |
| DLC Approved | Yes |
| DLC ID | PL2M6895FL33 |
| CEC Status | Lawful for sale in California |
| RoHS Compliant | Yes |
| NSF Approved | Yes - Approved |







