Presented By: **Candela Corporation** Contact Phone:

GE


Contact E-mail:


(800) 922-9226 sales@candelacorp.com



Lighting 21254 - 300R/3FL

GE R40 - Reflector Flood





CAUTIONS & WARNINGS

Warning

Risk of Fire

- Keep combustible materials away from lamp.
- Use in fixture rated for this product.
- Unexpected lamp rupture may cause injury, fire, or property damage - Avoid direct water/liquid contact.

NOTES

- Collector grid.
- Lamp base is a brass base (BB).
- Lamp is made of heat resistant glass (HRG).
- Light output is maintained best when burned within 45 degrees of vertically base up.

Customer Name: Project Name: Fixture Type:

GENERAL CHARACTERISTICS

Lamp Type Incandescent - Reflector Bulb R40 Base Mogul Screw (E39) Filament CC-2V **Bulb Finish** Frost Wattage 300 Voltage 120 Rated Life 2000 hrs **Bulb Material** Heat resistant glass **Base Material** Brass **Primary Application Reflector Flood**

PHOTOMETRIC CHARACTERISTICS

Initial Lumens 3000 Center Beam Candlepower 4500 (CBCP) Max. Beam Candlepower 4500 (MBCP) Nominal Initial Lumens per Watt 10

DIMENSIONS

Maximum Overall Length (MOL) Bulb Diameter (DIA) Bulb Diameter (DIA) (MAX)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

7.25 cm

5 cm

5 cm