



- Compatible with magnetic ballasts - DIRect installation
- Built-in universal voltage driver - BYPass installation
- Omni directional light distribution suitable for horizontal or vertical installations
- Replaces G24q & GX24q (4-pin) or G24d & GX24d (2-pin) 13W-26W CFL lamps

SPECIFICATIONS											
Product	Model	CCT	Lumens	CRI (typ.)	LPW	Dim	Equiv.	Beam Angle	Life (hrs)	Voltage	Encl.
34996	7PLO/827/HYBM	2700K	770	82	110	No	13-18W	360°	50,000	120-277V	Yes
34997	7PLO/830/HYBM	3000K	790	82	112	No	13-18W	360°	50,000	120-277V	Yes
34998	7PLO/835/HYBM	3500K	820	82	117	No	13-18W	360°	50,000	120-277V	Yes
34999	7PLO/840/HYBM	4000K	850	82	121	No	13-18W	360°	50,000	120-277V	Yes
35000	9PLO/827/HYBM	2700K	1,100	82	122	No	26W	360°	50,000	120-277V	Yes
35001	9PLO/830/HYBM	3000K	1,150	82	125	No	26W	360°	50,000	120-277V	Yes
35002	9PLO/835/HYBM	3500K	1,200	82	130	No	26W	360°	50,000	120-277V	Yes
35003	9PLO/840/HYBM	4000K	1,250	82	133	No	26W	360°	50,000	120-277V	Yes

3 Level power output



Power select switch allows light output to be tailored to application requirements and can be adjusted from high to low.



- Integral driver suitable for 120-277V
- E26 version is dimmable at 120V line voltage
- EX39 version has integrated side switch for field selectable lumen output
- Suitable for use in totally enclosed fixtures
- Integral 6kV surge protector

SPECIFICATIONS											
Product	Model	CCT	Lumens	CRI (typ.)	LPW	Dim	Equiv.	Beam Angle	Life (hrs)	Voltage	DLC
36165	17A21/830/277V/DIM	3000K	2,000	82	118	Yes	125W	230°	50,000	120-277V	N.A.
36166	17A21/835/277V/DIM	3500K	2,000	82	118	Yes	125W	230°	50,000	120-277V	N.A.
36167	17A21/840/277V/DIM	4000K	2,100	82	124	Yes	125W	230°	50,000	120-277V	N.A.
36168	17A21/850/277V/DIM	5000K	2,100	82	124	Yes	125W	230°	50,000	120-277V	N.A.
36169	24HID/830/277V/E26/DIM	3000K	3,100	82	129	Yes	200W	230°	50,000	120-277V	N.A.
36214	24HID/835/277V/E26/DIM	3500K	3,100	82	129	Yes	200W	230°	50,000	120-277V	N.A.
36170	24HID/840/277V/E26/DIM	4000K	3,200	82	133	Yes	200W	230°	50,000	120-277V	N.A.
36171	24HID/850/277V/E26/DIM	5000K	3,200	82	133	Yes	200W	230°	50,000	120-277V	N.A.
36158	24HID/830/277V/EX39/SD	3000K	3,100	82	129	No	200W	230°	50,000	120-277V	✓
36159	24HID/835/277V/EX39/SD	3500K	3,100	82	129	No	200W	230°	50,000	120-277V	✓
36160	24HID/840/277V/EX39/SD	4000K	3,200	82	133	No	200W	230°	50,000	120-277V	✓
36161	24HID/850/277V/EX39/SD	5000K	3,200	82	133	No	200W	230°	50,000	120-277V	✓
36172	34HID/830/277V/E26/DIM	3000K	4,500	82	132	Yes	300W	230°	50,000	120-277V	N.A.
36173	34HID/840/277V/E26/DIM	4000K	5,000	82	147	Yes	300W	230°	50,000	120-277V	N.A.
36174	34HID/850/277V/E26/DIM	5000K	5,000	82	147	Yes	300W	230°	50,000	120-277V	N.A.
36162	34HID/830/277V/EX39/SD	3000K	4,500	82	132	No	175W	230°	50,000	120-277V	✓
36163	34HID/840/277V/EX39/SD	4000K	5,000	82	147	No	175W	230°	50,000	120-277V	✓
36164	34HID/850/277V/EX39/SD	5000K	5,000	82	147	No	175W	230°	50,000	120-277V	✓
16325	E26 EXTENDER	E26 Lamp Extender Adds 1.30" (33mm) to Lamp Height									
35050	EX39 EXTENDER	EX39 Lamp Extender Adds 1.70" (43mm) to Lamp Height									
97718	10SURGE/277V	10kV Surge Protector									