Presented By: **Candela Corporation** (800) 922-9226

GE

Lighting


Contact Phone: Contact E-mail:


sales@candelacorp.com



19866 - 350PAR56/SP

GE PAR56 - Train; Locomotive





CAUTIONS & WARNINGS

Warning

Risk of Fire

- Keep combustible materials away from lamp.

- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
- Use in enclosed fixture rated for this product.

- Avoid direct water/liquid contact.

NOTES

• Lamp is made of heat resistant glass (HRG).

Customer Name: Project Name: Fixture Type:

GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament Wattage Voltage Rated Life **Primary Application**

Sealed Beam - PAR PAR56 Screw Terminals CC-8 350 75 500 hrs Train:Locomotive

PHOTOMETRIC CHARACTERISTICS

Initial Lumens 6200 Nominal Initial Lumens per Watt 17

DIMENSIONS

Maximum Overall Length (MOL) Bulb Diameter (DIA) Bulb Diameter (DIA) (MAX) 4.5000 in(114.3 mm) 7.000 in(177.8 mm) 7.000 in(177.8 mm)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168198660