

LINE NO.	LAMP NUMBER	PRIMARY APPLICATION	DESIGN VOLTS	DESIGN WATTS	DESIGN AMPS	APPROX. CANDLE-POWER	RATED AVERAGE LAB LIFE HOURS	BASE TYPE	MAXIMUM OVERALL LENGTH (inches)	LIGHT CENTER LENGTH (inches)	FILAMENT TYPE	FIG. NO.
T-1¾ Bulb 7/32" (5.5mm) Diameter (Continued)												
1	86*	Indicator	6.30	1.26	0.20	0.40	20,000	Wedge	0.800	0.400	C-2F	32
2	350*	Aircraft	6.30	0.95	0.15	0.40	3,000	S.C. Midget Flanged	0.625	0.375	C-2R	29
3	381*	Indicator	6.30	1.26	0.20	0.40	20,000	S.C. Midget Flanged	0.625	0.375	C-2F	29
4	2181*	Indicator	6.30	1.26	0.20	0.40	20,000	Wire Lead	0.520	—	C-2F	74
5	2112	Indicator	6.30	1.26	0.20	0.50	3,000	Wire Lead	0.520	—	C-2R	74
6	344*	Indicator	10.00	0.14	0.01	0.00	5,000	S.C. Midget Flanged	0.625	0.375	C-2F	29
7	367*	Indicator	10.00	0.40	0.04	0.10	5,000	S.C. Midget Flanged	0.625	0.375	C-2V	29
8	2309*	Special Service	10.00	0.40	0.04	0.10	5,000	Encapsulated	0.600	—	C-2V	31
9	384*	Indicator	11.00	0.28	0.03	0.05	2,000	S.C. Midget Flanged	0.625	—	C-2F	29
10	394*	Indicator	12.00	0.48	0.04	0.10	10,000	S.C. Midget Flanged	0.625	0.375	C-2F	29
11	17035	Instrument	12.00	1.20	0.10	0.48	1,000	BAX10ds	0.925	—	C-2V	88
12	17036	Indicator	12.00	1.20	0.10	0.48	1,000	BAX10ss	0.925	—	C-2V	89
13	17037	Indicator	12.00	1.20	0.10	0.48	1,000	W2x4.6d	0.780	0.570	C-2V	90
14	2723	Automotive	12.00	2.40	0.20	1.50	1,100	W2x4.6d	0.780	0.570	C-2V	90
15	17	Aircraft	28.00	1.82	0.07	0.65	500	Wedge	0.800	0.400	C-2F	32
16	18*	Automotive	14.00	0.56	0.04	0.13	5,000	Wedge	0.800	0.400	C-2F	32
17	73	Indicator	14.00	1.12	0.08	0.30	15,000	Wedge	0.800	0.400	C-2F	32
18	382	Indicator	14.00	1.12	0.08	0.30	50,000	S.C. Midget Flanged	0.625	0.375	C-2F	29
19	386	Indicator	14.00	1.12	0.08	0.30	40,000	Midget Grooved	0.625	0.375	C-2F	28
20	37	Automotive	14.00	1.26	0.09	0.50	2,500	Wedge	0.800	0.400	C-2F	32
21	PC37	Automotive	14.00	1.26	0.09	0.50	2,500	Printed Circuit	0.842	0.315	C-2F	33
22	330	Aircraft	14.00	1.12	0.08	0.50	750	S.C. Midget Flanged	0.625	0.375	C-2F	29
23	2162*	Indicator	14.00	1.40	0.10	0.50	10,000	Wire Lead	0.520	—	C-2F	74
24	74	Automotive	14.00	1.40	0.10	0.70	1,000	Wedge	0.800	0.400	C-2F	32
25	PC74	Automotive	14.00	1.40	0.10	0.70	1,000	Printed Circuit	0.842	0.315	C-2F	33
26	PC74S*	Automotive	14.00	1.40	0.10	0.70	1,000	Printed Circuit	0.842	0.315	C-2F	33
27	70	Automotive	14.00	2.10	0.15	1.50	100	Wedge	0.800	0.400	C-2F	32
28	11009	Courtesy, Dome	14.40	1.73	0.12	1.00	500	BA7s	0.748	—	—	34
29	370*	Indicator	18.00	0.72	0.04	0.15	10,000	S.C. Midget Flanged	0.625	0.375	C-2F	29
30	346*	Indicator	18.00	0.72	0.04	0.25	1,000	Midget Grooved	0.625	0.375	C-2F	28
31	17040	Automotive	24.00	1.20	0.05	0.48	1,000	W2x4.6d	0.780	0.570	C-2V	90
32	17061	Courtesy, Dome	24.00	3.12	0.13	0.60	200	BA7s	0.812	0.470	C-7A	34
33	327R*	Aircraft, Red	28.00	1.12	0.04	—	4,000	S.C. Midget Flanged	0.625	—	C-2F	29
34	85	Indicator	28.00	1.12	0.04	0.30	10,000	Wedge	0.800	0.400	C-2F	32
35	387	Indicator	28.00	1.12	0.04	0.30	25,000	S.C. Midget Flanged	0.625	0.375	C-2F	29
36	388*	Indicator	28.00	0.11	0.00	0.30	7,000	Midget Grooved	0.625	0.375	C-2F	28
37	327	Aircraft	28.00	1.12	0.04	0.33	4,000	S.C. Midget Flanged	0.625	0.375	C-2F	29
38	327X①*	Indicator	28.00	1.29	0.05	0.33	2,500	S.C. Midget Flanged	0.625	0.375	C-2F	29
39	334*	Aircraft	28.00	1.12	0.04	0.33	1,000	Midget Grooved	0.625	0.375	C-2F	28
40	2329*	Special Service	28.00	1.40	0.05	0.34	2,500	Encapsulated	0.600	—	C-2F	31
T-2¼ Bulb 9/32" (7.5mm) Diameter												
41	3886LL	Interior Automotive	12.00	6.00	0.50	6.36	3000	Ba9s	1.078	0.590	C-2R	93

① "X" is a special variant.

NOTE: CIM = Construction Industrial Machinery D.C. = Double Contact MP = Multipurpose Rt. = Right S.C. = Single Contact

***This part number is included for reference only and inventory may not be available.**