



WORLDWIDE PARTNER

[site search](#)[home](#)[products](#)[education / resources](#)

Commercial Products & Solutions

[lighting applications](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > 39585**39585 – 4042**

GE PAR36 - Emergency Building Light; Emergency Building

GENERAL CHARACTERISTICS

Lamp type	Sealed Beam - PAR
Bulb	PAR36
Base	Screw Terminals
Filament	C-6
Product Technology	Incandescent
Wattage	12
Voltage	6.4
Rated Life	150 hrs
Primary Application	Emergency Building Light; Emergency Building

PHOTOMETRIC CHARACTERISTICS


Beam Spread - Horizontal	45° - 10 %
Beam Spread - Vertical	20° - 10 %
Max. Beam Candlepower (MBCP) (MAX)	1100

DIMENSIONS

Maximum Overall Length (MOL)	2.7500 in (69.8 mm)
Bulb Diameter (DIA)	4.500 in (114.3 mm)

PRODUCT INFORMATION

Product Code	39585
Description	4042
ANSI Code	4042
Standard Package Case	
Standard Package GTIN	10043168395851
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168395854



Bulb



Base



Filament

[View Larger](#)**ADDITIONAL RESOURCES**[Catalogs](#)[Disposal Policies & Recycling Information](#)**ALSO AVAILABLE IN...**

Product Code	Description	Standard Package
39586	4042 BULK	Case

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997-2009