

INCANDESCENT LAMPS

Watts	Bulb	Base	Product Number	Symbols, Footnotes	Ordering Code	Volts	Pkg. Qty.:	Description	Class Filament	LCL (In.)	MOL (In.)	Rated Avg. Life (Hrs.)(93)	Approx. MBCP*	Lumens	
40	K19 R14	Med.	30728-0	▲	40K19/DL 6/2	120	12	Director	C, C-9		4%	1150		500	
			35454-8		40R14/SP	120	24	Light Fr. Mini. Refl.	C, CC-2V		2%	1500		250	
			13355-3		BC40R14N 6/1 TP	120	6	Light Fr. Mini. Refl.	C, CC-2V		2%	1500			
			16704-9		BC-40R14/SP 120V 6/1PKTP	120	6	Surge Proof Light Mini. Refl.	C, CC-2V		2%	1500		250	
	R16	Med.	13337-1		BC40R16/SP 6/1 TP	120	6	Surge Proof Light Mini. Refl.	C, CC-2V		3%	1500		250	
	S11	Inter.	21216-7	▲	BC40S11/NTP 16/1	120	16	Clear High Intensity	C, CC-2V		2%	500		440	
			14075-6		40S11N/IF PRO	130	24	ProPack Clear High Intensity	C, CC-2V		2%	500		420	
			24830-2	▲	40S11N/IF	120	24	Frost High Intensity	C, CC-2V		2%	500		420	
	T6½	Inter.	20491-7	▲	BC40T6-½/2 12/1	120	12	Clear Refrigerator	B, C-8		5½%	1000		350	
	T10	Med.	38989-0	▲	BC40T10/IF/TP 6/1	120	6	Frost Showcase	B, C-8		5%	1000		250	
			13814-9	▲	40T10/IF 24/1	120-130	24	Frost Showcase	B, C-8		5%	1000		435	
			38988-2	▲	BC40T10/TP 6/1	120	6	Clear Showcase	B, C-8		5%	1000		435	
			13815-6	▲	40T10 24/1	120-130	24	Clear Showcase	B, C-8		5%	1000		440	
			20184-8	▲	40T10/TG	120-130	24	TuffGuard Coated Clear Showcase	B, C-8		5%	1000		440	
			BR30	Med.	16751-0	▲ (87)	45BR30/FL55/LL 12/1	120	12	Long Life Reflector Flood	C, CC-6		5%	2500	
	45	R20	Med.	20323-2	▲ (87)	45R20/LL 12/1	120	12	Long Life Reflector Flood	C, CC-6		3½%	2500		385
20322-4				▲ (87)	45R20 12/1	130	12	Reflector Flood	C, CC-6		3½%	2000		380	
20324-0				(87)	45R20 12/1 PRO	130	12	ProPack Reflector Flood	C, CC-6		3½%	2000		380	
50				A19	Med.	14154-9	▲	50A	24	60	Frost Train	C, C-6		4%	1000
24569-6	▲	50A	250			120	Frost	C, RC-9		3½%	1000				
21952-7	▲	50A19/31	120			120	Clear Commercial Oven	B, C-9	2½%	3½%	1000		500		
37403-3	▲	50A/RS	120-130			120	Frost Rough Service Ratings @ 120V =47W	B, RC-9		3½%	1000		500		
20163-2	▲	50A/RS 12/2	120			24	Frost Rough Service	B, RC-9		3½%	1000		480		
24572-0	▲	50A/RS	250			120	Frost Rough Service	C, RC-9		3½%	1000		355		
14977-3	▲ (66)	50A/RS/TF	120-130			120	Frost Rough Service Silicone Coated	B, C-17A		3½%	1000				
BR30	Med.	24889-8	▲ (87)			50BR30/FL	120	12	Reflector Flood	C, CC-6		5%	2000		

For the most current product information, go to the e-catalog on www.philips.com
Incandescent symbols and footnotes located on page 149

