



LED Glass HID lamps

45GC/LED/830 EX39 BB 6/1

Philips Glass HID lamps offer you an easy, short-payback LED solution to replace High Intensity Discharge (HID) lamps. Thanks to our High-Power LED filament technology, this new generation of indoor/outdoor glass lamps brings all the energy-efficiency and long-lifetime benefits of LED to HID replacement, while providing instant savings with a low initial investment. They are designed to have the same aesthetics, lamp size and light distribution as the HID lamps they are replacing, so the upgrade to LED is easier than ever!

Product data

General Information		Power Consumption	
Cap-Base	EX39 [Exclusionary Mogul Screw]	Power Consumption	45 W
Nominal lifetime	50,000 hour(s)	Lamp Current (Max)	600 mA
Switching Cycle	50,000	Starting Time (Nom)	0.5 s
Lighting Technology	LED	Warm-up time to 60% light	0.5 s
		Power Factor (Fraction)	0.9
		Voltage (Nom)	120-277 V
		UL Type	HIB_UL Type B (UL Listed+Classified)
Light Technical		Temperature	
Color Code	830 [CCT of 3000K]	T-Case Maximum (Nom)	133 °F
Beam Angle (Nom)	300 degree(s)		
Luminous Flux	6,800 lm	Controls and Dimming	
Color Designation	White (WH)	Dimmable	Only with specific dimmers
Correlated Color Temperature (Nom)	3000 K		
Luminous Efficacy (rated) (Nom)	151 lm/W	Mechanical and Housing	
Color Consistency	<6	Bulb Finish	Clear
Color rendering index (CRI)	80	Bulb Shape	ED28
LLMF At End Of Nominal Lifetime (Nom)	70 %	Net Weight (Piece)	0.573 lb
Photobiological safety according to EN 62471	RG1		
Operating and Electrical			
Input Frequency	50 to 60 Hz		

LED Glass HID lamps

Approval and Application

Approval Marks	DLC compliance
EU RoHS compliant	Yes
Ambient temperature range	-4 to +113 °F

Application Conditions


can it be used in closed luminaires	Yes
-------------------------------------	-----

Product Data

Order product name	45GC/LED/830 EX39 BB 6/1
--------------------	--------------------------


Full product name	45GC/LED/830 EX39 BB 6/1
Order code	588228
Material Nr. (12NC)	929003773304
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677588229
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677588224

Dimensional drawing




Product	D	C
45GC/LED/830 EX39 BB 6/1	3-5/8 inch	9-9/16 inch

Photometric data



Light Distribution Diagram - 45GC/LED/830 EX39 BB 6/1



Spectral Power Distribution Colour - 45GC/LED/830 EX39 BB 6/1

