



- **HYBrid installation - DIRECT or BYPass**
- **Compatible with magnetic ballasts - DIRECT installation**
- **Built-in universal voltage driver - BYPass installation**
- **Exceptional efficacy**



- **Plug & Play installation (electronic ballasts only)**
- **Omni directional light distribution suitable for horizontal or vertical installations**
- **Replaces G24q & GX24q (4-pin) 13W-26W CFL lamps**
- **0-10V dimming ballast compatible**

SPECIFICATIONS											
Product	Model	CCT	Lumens	CRI (typ.)	LPW	Dim	Equiv.	Beam Angle	Life (hrs)	Voltage	Encl.
36627	3.5PLS/827/HYB/G23/R	2700K	325	82	93	No	7-9W	120°	50,000	120-277V	No
36628	3.5PLS/830/HYB/G23/R	3000K	340	82	97	No	7-9W	120°	50,000	120-277V	No
36629	3.5PLS/835/HYB/G23/R	3500K	350	82	100	No	7-9W	120°	50,000	120-277V	No
36630	3.5PLS/840/HYB/G23/R	4000K	370	82	106	No	7-9W	120°	50,000	120-277V	No
98403	5.5PLSV/827/HYB/GX23	2700K	570	82	104	No	13W	120°	50,000	120-277V	No
98404	5.5PLSV/830/HYB/GX23	3000K	600	82	109	No	13W	120°	50,000	120-277V	No
98405	5.5PLSV/835/HYB/GX23	3500K	600	82	109	No	13W	120°	50,000	120-277V	No
98406	5.5PLSV/840/HYB/GX23	4000K	620	82	113	No	13W	120°	50,000	120-277V	No
36644	5.5PLSH/827/HYB/GX23/R	2700K	570	82	104	No	13W	110°	50,000	120-277V	No
36645	5.5PLSH/830/HYB/GX23/R	3000K	580	82	105	No	13W	110°	50,000	120-277V	No
36646	5.5PLSH/835/HYB/GX23/R	3500K	600	82	109	No	13W	110°	50,000	120-277V	No
36647	5.5PLSH/840/HYB/GX23/R	4000K	620	82	113	No	13W	110°	50,000	120-277V	No
36632	5.5PLS/827/HYB/GX23/R	2700K	520	82	95	No	13W	120°	50,000	120-277V	No
36633	5.5PLS/830/HYB/GX23/R	3000K	550	82	100	No	13W	120°	50,000	120-277V	No
36634	5.5PLS/835/HYB/GX23/R	3500K	600	82	109	No	13W	120°	50,000	120-277V	No
36635	5.5PLS/840/HYB/GX23/R	4000K	620	82	113	No	13W	120°	50,000	120-277V	No

SPECIFICATIONS											
Product	Model	CCT	Lumens	CRI (typ.)	LPW	Dim	Equiv.	Beam Angle	Life (hrs)	Voltage	Encl.
34988	6.5PLO/827/DIR	2700K	720	82	110	Yes	13-18W	360°	50,000	120-277V	Yes
34989	6.5PLO/830/DIR	3000K	740	82	113	Yes	13-18W	360°	50,000	120-277V	Yes
34990	6.5PLO/835/DIR	3500K	780	82	120	Yes	13-18W	360°	50,000	120-277V	Yes
34991	6.5PLO/840/DIR	4000K	800	82	123	Yes	13-18W	360°	50,000	120-277V	Yes
34992	9.5PLO/827/DIR	2700K	1,050	82	110	Yes	26W	360°	50,000	120-277V	Yes
34993	9.5PLO/830/DIR	3000K	1,100	82	115	Yes	26W	360°	50,000	120-277V	Yes
34994	9.5PLO/835/DIR	3500K	1,150	82	121	Yes	26W	360°	50,000	120-277V	Yes
34995	9.5PLO/840/DIR	4000K	1,200	82	126	Yes	26W	360°	50,000	120-277V	Yes