



JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE	
51	7.5	.220	1.00	12.57	1,000	C-2R	
53	14.4	.120	1.00	12.57	1,000	C-2V	
1445	14.4	.135	.70	8.80	2,000	C-2V	
1445	18.0	.150	1.50	18.86	250	C-2V	
1450	24.0	.035	.23	2.89	3,000	C-2F	
356	28.0	.170	3.50	44.00	500	C-2F	

		METRIC DIMENSIONS ARE IN MILLIMETERS		. I. K. I				TON			
			TOLERANCE UNLESS OTHERWISE SPECIFIED								
				1 PL +/- 0.2		TITLE					
			THIRD ANGLE	2 PL +/- 0.20		G∹	G-3 1/2 SINGLE CONTACT BAYONET BAS				
			PROJECTION	ANGLE +/-							
			DRAWN BY	APPV'D BY	DATE	SIZE		DRAWING			
			L. WENGSTROM	QC 3.	/8/01	Α	55335	NO. BAYONI	ET SINGLE CO	NTACT G	3-3 1/2
	RELEASED AS CAD	3/8/01	- CAD D	IVAVIII4O -		SCALE	1	RELEASED	REVISION	REV.	SHEET
REV.	DESCRIPTION/ECO	APPV'D						DATE 3/8/01	DATE	NO.	4 4
NO.	NUMBER	DATE	MANUAL REVISIONS NOT PERMITTED			NONE	3/0/01		1	I OF I	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

JKL Components:

53 JKL-53