



- Suitable to replace 20W, 35W, 50W, 60W halogen MR16 lamps
- Compatible with most low-voltage electronic transformers
- Smooth dimming with most forward and reverse phase dimming controls
- Suitable for use in totally enclosed fixtures



SPECIFICATIONS													
Product	Model	CCT	Lumens	CRI (typ.)	LPW	CBCP	Dim	Equiv.	Beam Angle	Life (hrs)	Voltage	Encl.	ES / JA8 / T20
36200	6.5MR16DIM/827NF25/35W	2700K	460	82	71	1,610	Yes	35W	25°	25,000	12V	Yes	✓ / N.A. / N.A.
36201	6.5MR16DIM/830NF25/35W	3000K	460	82	71	1,610	Yes	35W	25°	25,000	12V	Yes	✓ / N.A. / N.A.
36202	6.5MR16DIM/827FL35/35W	2700K	460	82	71	910	Yes	35W	35°	25,000	12V	Yes	✓ / N.A. / N.A.
36203	6.5MR16DIM/830FL35/35W	3000K	460	82	71	910	Yes	35W	35°	25,000	12V	Yes	✓ / N.A. / N.A.
36204	6.5MR16DIM/927NF25	2700K	500	92	77	2,350	Yes	50W	25°	25,000	12V	Yes	✓ / ✓ / ✓
36205	6.5MR16DIM/930NF25	3000K	520	92	80	2,400	Yes	50W	25°	25,000	12V	Yes	✓ / ✓ / ✓
36206	6.5MR16DIM/940NF25	4000K	540	92	83	2,450	Yes	50W	25°	25,000	12V	Yes	✓ / ✓ / ✓
36207	6.5MR16DIM/927FL35	2700K	500	92	77	1,350	Yes	50W	35°	25,000	12V	Yes	✓ / ✓ / ✓
36208	6.5MR16DIM/930FL35	3000K	520	92	80	1,400	Yes	50W	35°	25,000	12V	Yes	✓ / ✓ / ✓
36209	6.5MR16DIM/940FL35	4000K	540	92	83	1,450	Yes	50W	35°	25,000	12V	Yes	✓ / ✓ / ✓
36210	6GU10DIM/827FL40	2700K	550	82	92	700	Yes	50W	40°	25,000	120V	Yes	✓ / N.A. / N.A.
36211	6GU10DIM/830FL40	3000K	570	82	95	750	Yes	50W	40°	25,000	120V	Yes	✓ / N.A. / N.A.
36212	6PAR16DIM/827FL35/RC	2700K	550	82	92	1,000	Yes	60W	35°	25,000	120V	Yes	✓ / N.A. / N.A.
36213	6PAR16DIM/830FL35/RC	3000K	570	82	95	1,050	Yes	60W	35°	25,000	120V	Yes	✓ / N.A. / N.A.
57984	6MR16DIM/827FL35/R	2700K	480	82	80	1,350	Yes	50W	35°	25,000	12V	Yes	✓ / N.A. / N.A.
57985	6MR16DIM/830FL35/R	3000K	500	82	83	1,400	Yes	50W	35°	25,000	12V	Yes	✓ / N.A. / N.A.
57986	6MR16DIM/840FL35/R	4000K	520	82	86	1,450	Yes	50W	35°	25,000	12V	Yes	✓ / N.A. / N.A.
57991	6PAR16DIM/830FL35/R	3000K	500	82	83	1,050	Yes	60W	35°	25,000	120V	Yes	✓ / N.A. / N.A.