

## 72550 - GE saf-t-gard® 75/67 watt A21 1-pack

### 75A/RS/STG-TP6 130

- ☞ 130/120 volts
- ☞ 2800K soft white light appearance
- ☞ A21 shape with medium base for use in rough service applications
- ☞ GE saf-t-gard® bulbs feature a protective Teflon® coating that helps contain glass fragments if broken. Designed with heavy-duty, all-weather construction, these bulbs protect against shattering, rain breakage and splatter from oil and lubricants. GE saf-t-gard® bulbs are perfect for home use in kitchens, basements garages, workshops and enclosed exterior fixtures
- ☞ Estimated yearly energy costs \$9.03/\$8.07 based on 3 hours per day \$0.11 per kWh
- ☞ Lasts 1.8/4.9 years based on 3 hours per day usage
- ☞ Provides 560/740 lumens

### PRODUCT PHOTO



### GENERAL CHARACTERISTICS

Base Description	Medium Screw
Base Type	Screw-In
Bulb Finishes and Colors	Inside frost
Filament	C-7A
Life in Years	1.82 yr
Rated Life Hours-nominal	2000 h
Primary Application	Standard <General Purpose>
Bulb Material	Soft glass
Product Technology	Incandescent
Lamp Count	1
Requested Structure	Carton
Base	E26/24
Bulb Shape	A19

### PHOTOMETRIC CHARACTERISTICS

Nominal Initial Lumen per Watt	9.4
Initial Lumens-nominal	705 lm

### PRODUCT INFORMATION

Product Code	72550
Description	75A/RS/STG-TP6 130
Alternative Unit Of Measure	CASE
Standard Package Quantity	6
Ean UPC	043168725507
Standard Package GTIN	00043168725507
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	6
Sales Unit	Case
UCC	043168725507
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168725507
Standard Package GTIN	10043168725504
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168725507

### DIMENSIONS

Diameter	2.62 in
----------	---------

### ELECTRICAL CHARACTERISTICS

Wattage	75 W
Estimated Energy Cost per Year	9.03 \$
Input Voltage [nom]	130 W
Rated power (Watts)	75 W