

FILAMENT LINE



Suitable for All Decorative Applications

- Micro-designed driver - No heatsink required
- Provides comfortable, diffused light
- Dimmable with forward and reverse phase controls
- Most models are suitable for wet locations

PREMIUM FILAMENT LINE



Suitable for All Decorative Applications

- Suitable for use in wet locations
- 320° omnidirectional beam angle
- High CRI and R values (R9 53, R13 93)
- Smooth dimming with most forward and reverse phase controls

SPECIFICATIONS												
Product	Model	CCT	Lumens	CRI (typ.)	LPW	Dim	Equiv.	Beam Angle	Life (hrs)	Voltage	Finish	ES / T20
98458	1FS14/820/A	2000K	35	82	75	Yes	10W	300°	15,000	120V	Amber	N.A. / N.A.
98457	1FS14/827	2700K	55	82	37	Yes	10W	300°	15,000	120V	Clear	N.A. / N.A.
57946	3.5FT10DIM/822/A	2200K	250	82	90	Yes	25W	330°	15,000	120V	Amber	N.A. / N.A.
98240	4.5FBA11DIM/820/FT/A	2000K	240	82	68	Yes	40W	300°	15,000	120V	Amber	N.A. / N.A.
98241	3.3FB11DIM/927	2700K	300	92	90	Yes	40W	300°	15,000	120V	Clear	✓ / ✓
98454	5FB11DIM/827	2700K	500	82	107	Yes	60W	300°	15,000	120V	Clear	N.A. / N.A.
98455	5FB11DIM/827/E26	2700K	500	82	93	Yes	60W	300°	15,000	120V	Clear	✓ / N.A.
98239	4FST19DIM/820/A	2000K	300	82	90	Yes	40W	300°	15,000	120V	Amber	N.A. / N.A.
98376	5FA19DIM/827	2700K	450	82	63	Yes	40W	300°	15,000	120V	Clear	N.A. / N.A.
98448	7.5FA19DIM/820/A	2000K	600	82	94	Yes	60W	300°	15,000	120V	Amber	N.A. / N.A.
98278	7.5FA19DIM/827	2700K	800	82	91	Yes	60W	300°	15,000	120V	Clear	✓ / N.A.
98449	7.5FA19DIM827/FR	2700K	800	82	91	Yes	60W	300°	15,000	120V	Frosted	N.A. / N.A.
98358	7.5FA19DIM/827/SB	2700K	700	82	53	Yes	60W	N.A.	15,000	120V	Silver Bowl	N.A. / N.A.
98279	9FA19DIM/927	2700K	810	92	79	Yes	60W	300°	15,000	120V	Clear	✓ / ✓
98451	4FG16.5DIM/827	2700K	350	82	100	Yes	40W	300°	15,000	120V	Clear	N.A. / N.A.
97826	4.5FG25DIM/827/SB	2700K	400	82	63	Yes	40W	N.A.	15,000	120V	Silver Bowl	N.A. / N.A.
57945	5FG40DIM/827	2700K	470	82	35	No	40W	330°	15,000	120V	Clear	✓ / N.A.

SPECIFICATIONS												
Product	Model	CCT	Lumens	CRI (typ.)	LPW	Dim	Equiv.	Beam Angle	Life (hrs)	Voltage	Finish	ES / T20
36075	3FT6DIM/820/A/R	2000K	110	82	37	Yes	25W	320°	15,000	120V	Amber	N.A. / N.A.
36077	1FS14/827/R	2700K	55	82	55	No	11W	320°	15,000	120V	Clear	N.A. / N.A.
36078	1FS14/820/A/R	2000K	35	82	35	No	11W	320°	15,000	120V	Amber	N.A. / N.A.
36079	5FA19DIM/927/R	2700K	450	92	90	Yes	40W	320°	15,000	120V	Clear	✓ / ✓
36080	5FA19DIM/927/FR/R	2700K	450	92	90	Yes	40W	320°	15,000	120V	Frosted	✓ / ✓
36081	5FA19DIM/820/A/R	2000K	340	82	68	Yes	40W	320°	15,000	120V	Amber	N.A. / N.A.
36082	9FA19DIM/927/R	2700K	810	92	90	Yes	60W	320°	15,000	120V	Clear	✓ / ✓
36083	9FA19DIM/927/FR/R	2700K	810	92	89	Yes	60W	320°	15,000	120V	Frosted	✓ / ✓
36085	7.5FA19DIM/827/SB/R	2700K	700	82	93	Yes	60W	320°	15,000	120V	Silver Bowl	N.A. / N.A.
36061	3.3FB11DIM/927/R	2700K	300	92	91	Yes	40W	320°	15,000	120V	Clear	✓ / ✓
36062	3.3FB11DIM/927/E26/R	2700K	300	92	91	Yes	40W	320°	15,000	120V	Clear	✓ / ✓
36063	3.3FB11DIM/927/FR/R	2700K	300	92	91	Yes	40W	320°	15,000	120V	Frosted	✓ / ✓
36064	5.5FB11DIM/927/R	2700K	500	92	91	Yes	60W	320°	15,000	120V	Clear	✓ / ✓
36065	5.5FB11DIM/927/E26/R	2700K	500	92	91	Yes	60W	320°	15,000	120V	Clear	✓ / ✓
36066	3.5FBA11DIM/820/FT/A/R	2000K	240	82	69	Yes	40W	320°	15,000	120V	Amber	N.A. / N.A.
36067	3.8FG16.5DIM/927/R	2700K	350	92	91	Yes	40W	320°	15,000	120V	Clear	✓ / ✓
36068	3.8FG16.5DIM/927/E26/R	2700K	350	92	91	Yes	40W	320°	15,000	120V	Clear	✓ / ✓
36069	4FG16.5DIM/820/A/R	2000K	250	82	63	Yes	40W	320°	15,000	120V	Amber	N.A. / N.A.
36070	3.8FG25DIM/927/R	2700K	350	92	92	Yes	40W	320°	15,000	120V	Clear	✓ / ✓
36071	4FG25DIM/820/A/R	2000K	250	82	63	Yes	40W	320°	15,000	120V	Amber	N.A. / N.A.
36072	4.5FG25DIM/827/SB/R	2700K	400	82	89	Yes	40W	320°	15,000	120V	Silver Bowl	N.A. / N.A.
36073	5.5FG40DIM/927/R	2700K	500	92	91	Yes	60W	320°	15,000	120V	Clear	✓ / ✓