




*** 22381 - 3 Light**
*** 22382 - 4 Light**
Black Harness Set

Candelabra Base
 Fits 3/4" Hole
 Includes Lock Nuts
 SPT-2, 18 Gauge,
 105° Leads
 75 Watts Max.
 Per Socket
 125 Volts
 6 1/4" Between Sockets
 12" on End Height - 1 1/4"



*** 22380**
1 Light
Harness Set

Candelabra Base
 Fits 3/4" Hole
 Includes Lock Nut
 12" Wire Leads
 SPT-2, 18 Gauge,
 105° Leads
 75 Watts Max., 125 Volts
 Height - 1 1/4"



*** 22377 - 18" Leads**
Candelabra Base

1/8-IP Hickey
 18 Gauge, 105° Leads
 75 Watts Max., 125 Volts
 Height - 1 1/4"



*** 22221**
Pigtail Holder

6" Wire Leads
 Medium Base
 14 Gauge 105° Leads
 660 Watts Max., 250 Volts
 Height - 1 1/2"



*** 22220**
Pigtail
 24" Wire Leads
 Candelabra Base
 18-2, SPT-1
 105° Leads
 75 Watts Max.
 Height - 1 1/8"



*** 22223**
Snap-In Pigtail
 24" Wire Leads
 Candelabra Base
 Snaps Into
 1" Diameter Hole
 18-2, SPT-1, 105° Leads
 75 Watts Max.
 Height - 1 1/8"



*** 22215**
Medium Base
 6" Wire Leads and
 Straight Bracket
 18 Gauge, 105° Leads
 Bracket Extends 1 1/8"
 Measured Center
 to Center
 660 Watts Max.
 250 Volts
 Height - 1 1/2"



*** 22203**
Medium Base
 1/8-IP Hickey
 660 Watts Max.
 250 Volts
 Height - 2"



*** 22200**
Pin Type With Cap
 Candelabra Base
 Use with SPT-1 Wire
 75 Watts Max.
 125 Volts
 Height - 1 1/4"



*** 22213**
Medium Base
 6" Wire Leads
 Fits 1 1/4" Hole
 18 Gauge, 105° Leads
 660 Watts Max.
 250 Volts
 Height - 1 1/2"



*** 22214**
Medium Base
 6" Wire Leads and
 Ground Wire
 Fits 3/8" x 1/4" Hole
 18 Gauge, 105° Leads
 660 Watts Max.
 250 Volts
 Height - 2"



*** 22217**
Medium Base
 9" Wire Leads
 Fits 3/8" x 1/4" Hole
 18 Gauge, 105° Leads
 660 Watts Max.
 250 Volts
 Height - 1 1/2"



*** 22216**
Medium Base
 9" Wire Leads
 1/8-IP Hickey
 18 Gauge, 105° Leads
 660 Watts Max.
 250 Volts
 Height - 1 1/8"



*** 22222**
Pin-Type Socket
 Medium Base
 Use with SPT-2 Wire
 660 Watts Max.
 250 Volts
 with Hanger Bracket
 Height - 2"

*Bulk Pack

CARDED PRODUCT SOLD IN INNER PACK ONLY