LED Traditional Wall Pack 3000 Lumens with Light Sensor

8.2"H x 12.5"W x 8.2"D





AC Electronics LED Retrofit Kit + Housing vs. Standard HID Lights						
Wall Pack Light Source	Input Wattage	Lifespan Hrs/Yrs	Energy Use (24hrs/day) Annual	Annual Cost (maintenance + electricity) @ \$0.11/kWh	Electrical Cost Savings	
HID	165	24,000/2.7	1446 kWh	\$159.00		
LED	37	50,000/5.7	324 kWh	\$35.65	78%	


Model Number AC106/35/1.0L



Specification

Includes:

- Single-Output Channel, Class 2 LED Driver, Model Number: AC-35C1.0AUA
- 1 PCB LED Array with 10 Samsung LH351B LEDs mounted to industrial grade aluminum LED bracket



Specifications Item

Specification	
120-277V, 50/60 Hz	
74	V
5000K	_
3000	*
80 lumen/Watt	fr
≥79% @ 7 years	yε
Not Measured	ye
7 years*	m
10	in
81.5°C	
37W	
84%	Tl
>0.9	in
<20%	CC
57°C	
<24dB	E١
FCC part 15	th
45°C Ambient	
-40°C Ambient	
8.2"H x 12.5"W x 8.2"D /7lbs	
	120-277V, 50/60 Hz 74 5000K 3000 80 lumen/Watt ≥79% @ 7 years Not Measured 7 years* 10 81.5°C 37W 84% >0.9 <20% 57°C <24dB FCC part 15 45°C Ambient -40°C Ambient

Warranty

* AC warrants to the purchaser that this fixture will be free from defects in material or workmanship for a period of 7 years from date of manufacture, when operated at a maximum ambient temperature of 110°F or 45°C, when properly installed and under normal conditions of use.

The warranty excludes damage resulting from improper installation or damage caused by fire or severe weather conditions including, but not limited to, lightning and storms. Evidence of direct exposure to water on the failed units voids the warranty.