

# BHC/DYS/DYV-5



#### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Product datasheet

#### Technical data

### **General product information**

Product Number	54835		
Product Name	BHCDYSDYV5 125V 24/CS 1/SKU		
Ordering Abbreviation	BHC/DYS/DYV-5		
Brand Name	OSRAM		
General Description	600 watt, tungsten halogen, medium to high voltage, single-ended		
Application	Projector, Microfilm, Stage & Studio		
Product Remark	<ul><li>Lamp has monoplane filament.</li><li>s (Operating Position) = Vertical, base down</li></ul>		

### **Electrical data**

Nominal Wattage	600 W
Nominal Voltage	125 V
Type of Current	AC

# Light technical data

Luminous Flux	17500 lm		
Light Center Length - LCL (in)	1.424 in		
Light Center Length - LCL (mm)	36.5 mm		
Color Temperature	3200 K		
Color Rendering Index	100		
Average Rated Life	75 h		

## Physical attributes

Bulb Shape	T6
Maximum Overall Length (in)	2.477 in
Maximum Overall Length (mm)	63.5 mm
Length I (in)	2.477 in
Length I (mm)	63.5 mm
Length l max. (in)	2.477 in
Length l max. (mm)	63.5 mm
Diameter d (in)	0.787 in
Diameter d (mm)	20.00 mm
Distance a (in)	1.424 in
Distance a (mm)	36.5 mm
Filament	CC-6

### Product datasheet

### Additional product data

Operating Position	s 90
Class	C (gas)
Lamp Type	SINGLE END

#### **Packaging Information**

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54835	0046135548352	Folding box (SKU)	1		
54835	10046135548359	Shipping box (Case)	24	8.3 in x 5.6 in x 4.5 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.