



STARLED[®], INC.

BI-PIN INDICATOR LIGHT CARTRIDGE (MOUNTING DIA. HOLE IS 0.290")

ORDERING INFORMATION: BPC14 1 F C 1 - 24V/25 - B
 (A) (B) (C) (D) (E) (F) (G)

(A) MODEL & LENGTH

BPC14 – L= 1.140" MAX. M.O.L.
 BPCL14 – L= 1.328" MAX. M.O.L.

(B) NUMBER OF LED CHIPS

1= 1, T-1¼ SINGLE CHIP LED
 6= 1, T-1¼ 6 CHIP LED

(C) LENS CAP TYPE

F= FLUTED
 P= PLAIN

(D) LENS CAP COLOR

C= CLEAR TINTED
 WC= WATER CLEAR
 WD= WHITE DIFFUSE

(E) LED EMITTING COLOR & WAVELENGTH

- 1= ULTRA RED (660nm)
- 2= STD. RED (630-635nm)
- U2= ULTRA HI EFF. RED (623-630nm)
- 3= STD. ORANGE (605-610nm)
- U3= ULTRA ORANGE (612-620nm)
- U4= ULTRA YELLOW (590-595nm)
- 5= STD. GREEN (565-570nm)
- *6NW= ULTRA PURE GREEN (520-530nm) (Single chip LED only)
- *8NW= FLUORESCENT "WHITE" (NO nm VALUE) (Single chip LED only)
- *10NW= ULTRA BLUE (465-475nm) (Single chip LED only)
- *11NW= BLUISH GREEN (498-508nm) (Single chip LED only)
- *12NW= SOFT WHITE (NO nm VALUE)

NOTE: *MAX CONTINUOUS CURRENT 10mA.

* NOT AVAILABLE IN 6 CHIP LED.

(F) STANDARD OPERATING VOLTAGES /mA.

SINGLE CHIP LED: 5V/25, 12V/25, 24V/25, 28V/25, 48V/12 & 120VAC/6
6 CHIPS LED: 12V/30, 24V/15, 28V/15, 48V/12 & 120VAC/6
FOR OTHER VOLTAGES PLEASE CALL FACTORY

(G) HOUSING COLOR

B = BLACK

MOUNTING CLIP SOLD SEPARATELY.

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

