



# MasterColor CDM-TC T4

MasterColor CDM-TC 70W/830 T4 CL

MasterColor CDM lamp gives a unique combination of unbeatable light quality and consistent performance over lifetime while keeping running costs low. The Philips MasterColor Tubular Single-Ended T4 lamp is a compact, energy efficient, ceramic metal halide lamp that provides crisp, sparkling light.

## Product data

### • General Characteristics

Base	G8.5
Bulb	T4 [T 14 mm]
Bulb Material	FadeBlock Quartz
Bulb Finish	Clear
Operating Position	Universal [Any or Universal (U)]
Life to 5% failures EL	6000 hr
Life to 10% failures EL	8000 hr
Life to 20% failures EL	9000 hr
Avg. Hrs. Life	12000 hr

### • Light Technical Characteristics

Color Code	830 [CCT of 3000K]
Color Rendering Index	83 Ra8
Color Designation	Warm White
Color Temperature	3000 K
Color Temperature technical	2915 K
Initial Lumens	6400 Lm
Luminous Efficacy Lamp EL	88 Lm/W
Lumen Maintenance EL 2000h	85 %
Lumen Maintenance EL 5000h	75 %
Lumen Maintenance EL 10000h	65 %
Design Mean Lumens EL	5100 Lm
Chromaticity Coordinate X	0.439 -
Chromaticity Coordinate Y	0.398 -

### • Electrical Characteristics

System Power EL	83 W
Watts	70 W
Lamp Wattage EL 25°C, Rated	73.0 W
Lamp Wattage EL 25°C, Nominal	70.0 W
Lamp Voltage	83 V
Lamp Current EL	0.87 A
Ignition Time	30 (max) s
Run-up time 90%	3 (max) min
Ignition Peak Voltage	3500 (min) V
Re-ignition Time [min]	15 (max) min
Dimmable	No

### • Environmental Characteristics

Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content	4.5 mg
Energy consumption kWh/1000h	80 kWh

### • UV-related Characteristics

Damage Factor D/fc PET (NIOSH)	0.3 (max) - 8 (min) h500lx
--------------------------------	----------------------------

### • Luminaire Design Requirements

Pinch Temperature	300 (max) C
Bulb Temperature	550 (max) C

**PHILIPS**

# MasterColor CDM-TC T4

## • Product Dimensions

Overall Length C	85 (max) mm
Diameter D	15 (max) mm
Light Center Length L	51 (min), 52 (nom), 53 (max) mm
Arc Length O	7 mm
Light Center Length L	2 in
Max Overall Length (MOL) - C	3.34375 (max) in
Diameter D	0.5 in

## • Product Data

Product number	373738
----------------	--------


Full product name	MasterColor CDM-TC 70W/830 T4 CL
Short product name	CDM-TC 70W/830 G8.5 T4 CL
Pieces per Sku	1
eop_pck_cfg	12
Skus/Case	12
Bar code on pack	46677373733
Bar code on case	50046677373738
Logistics code(s)	928086505115
tpd_ilcos_cd	MT/UB-70/830-H-G8.5-17/85
eop_net_weight_pp	0.010 kg

## Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will


remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

## Dimensional drawing




## MasterColor CDM-TC 70W/830 T4 CL

Product	C (Max)	D (Max)	L (Min)	L (Norm)	L (Max)	O (Norm)
CDM-TC 70W/830 G8.5	85	15	51	52	53	7



G8.5

## Photometric data



© 2014 Koninklijke Philips N.V. (Royal Philips)  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2014, November 27  
data subject to change