

Product 20314 Number:

CF13DS/E/827 Order

Abbreviation:

General DULUX 13W single compact fluorescent lamp with 4-pin base, 2700K, 82 CRI, for use with electronic and

Description: dimming ballasts

Product Information	
CF13DSE827 50/CS 1/SKU	
10000	
2GX7	
S (T4)	
82	
2700	
0.000	
0.00	
Dulux® S/E	
800	
688	
6.2	
157	
13.00	



Footnotes

- Approximate initial lumens after 100 hours operation.
 Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- There is a NEMAsupported, industry issue where T2, T4, and T5 fluorescent and compact fluorescent lamps operated on high frequency ballasts may experience an abnormal end-of-life phenomenon. This end-of-life phenomenon can resultin one or both of the following: 1. Bulb wall cracking near the lamp base. 2. The lamp can overheat in the base area and possibly melt the base and socket. NEMArecommends that high frequency compact fluorescent ballasts have an end-of-life shutdown circuit which will safely and reliably shut down the system in the rare event of an abnormal end-of-life failure mode described above. The final requirements of this system are yet to be defined by ANSI. For additional information refer to NEMApapers on their WEBSITE at www.NEMA.org.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is
- increased, there will be a corresponding increase in the average hours life.
 Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.