

PRODUCT DATASHEET

DULUX T/E XT 26W 835

SYLVANIA DULUX® T-E-IN ECOLOGIC® Family of Lamps 4-Pin Amalgam Compact Fluorescent Lamps: EXTENDED Life & EXTENDED Life SUPERSAVER | Amalgam CFL lamps with extended life and stable output across temperatures



Areas of application

- Recessed downlights
- Surface mounted luminaires
- Wall sconces

Product features

- The triple tube configuration of these lamps allows for single-lamp luminaire designs with improved efficacy & photometric performance
- XL lamps are direct replacements for standard lamps & provide up to 67 % longer life
- XL/SS lamps have improved lumen output of 6 % of the standard life SS lamps
- Improved lumen output vs. non-amalgam triple tube lamps
- Maintains 90 % lumens from 40 ° to 140 °F ambient
- Long average rated life of 26,000 hrs at 3 hrs/start and 30,000 hrs at 12 hrs/start
- Rare earth tri-phosphor with 82 CRI
- Less power consumption than incandescent lamps with comparable light output



TECHNICAL DATA

Additional product data

Base	GX24q-3
Mercury content	2.0 mg
Ordering Abbreviation	CF26DT/E/IN/835/XL/ECO
Abbrev. With Packaging Info.	CF26DTEIN835XLECO 50/CS 1/SKU
UPC Code	0046135213892
NAED	21389
Family Brand Name	Dulux® T/E XL
General Description	DULUX 26W CFL triple XL, eXtended Life amalgum lamp, 4 pin base, 3500K, 82 CRI, for use with electronic and dimming ballasts, ECOLOGIC

Electrical data

Nominal Wattage	26.00 W
Nominal voltage	80.00 V

Photometrical data

Lumens	1800 lm
Luminous flux at 25 °C	2400 lm
Color Temperature/CCT	3500 K
Color Rendering Index (CRI)	82
Light color	835

Dimensions & Weight

Overall length	126.01 mm
Length with base excl. base pins/connection	131,00 mm
Diameter	1.93 in
Product weight	0.12 lb

Materials & Colors

Lamp Finish	Coated
Bulb	T4

Application & Mounting

Dimming	Yes
---------	-----

Lifespan

Service life	18000 h
Average Rated Life (hr)	26000

Capabilities

Dimming	Yes
---------	-----

Country-specific categorizations

Order reference	26W/835 IN GX24
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	GX24q-3
Length	4.96 in
Height	1.93 in
Width	1.93 in

Safety advice

- 4-pin lamps are designed for use with programmed rapid start ballasts. Not recommended for use with IS ballasts.
- Minimum starting temperature depends on ballast used.
- Rule of thumb: to estimate the appropriate compact fluorescent lamp wattage, divide the incandescent wattage by 4.
- Equipment manufacturers are advised to consult the relevant ANSI and IEC standards for the maximum allowable dimensions and temperature to insure compatibility with similar products.
- For horizontal operation, install lamp with etch facing down.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.