



Product Number: 21272

Order Abbreviation: CF9DS/827/ECO

General Description: DULUX 9W single compact fluorescent lamp with 2-pin base, 2700K color temperature, 82 CRI, ECOLOGIC for use on magnetic ballast

Product Information	
Abbrev. With Packaging Info.	CF9DS827ECO 50/CS 1/SKU
Average Rated Life (hr)	10000
Base	G23
Bulb	S (T4)
Color Rendering Index (CRI)	80
Color Temperature/CCT (K)	2700
Diameter (in)	0.000
Diameter (mm)	0.00
Initial Lumens at 25C	600
Nominal Wattage (W)	9.00

Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- SYLVANIA ECOLOGIC fluorescent lamps are designed to pass the Federal Toxic Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states. TCLP test results are available upon request. Lamp disposal regulations may vary, check your local & state regulations. For more information, please visit www.lamprecycle.org
- SAFELINE lamps are intended for indoor use only. Lamps must be used in ambient temperatures below 135 degrees F. For T8 and T12 lamps, the coating is designed to withstand constant operating temperatures up to 239 degrees F and has a melting point in excess of 500 degrees F. For T5 lamps, the coating is designed to withstand constant operating

temperatures up to 500 degrees F and has a melting point in excess of 620 degrees F. Lamps must be used in open fixtures with sockets that provide adequate lamp pin to socket contact. Lamps must not be used with defective ballasts sockets, or fixtures with improper wiring.