



ACCESSORIES			
ORDER CODE	MODEL NUMBER	DESCRIPTION	ACCESSORIES IMAGE
108133	RMHYTHRC-05	REMOTE CTRL PROGRAMMING HC403VRC/ HC419VRC	
1409168	CPL-15SQ-PLATE	CPL SERIES ALUMINUM BEAUTY PLATE FOR 15" X 15" SQUARE HOLES, BRONZE*	

*See page 7 for CPL Cover Plate dimensions

SPECIFICATIONS:

ITEM	SPECIFICATION	CPL20AUX50XXX	CPL30AUX50XXX	CPL40AUX50XXX	CPL58AUX50XXX
		DETAILS			
GENERAL PERFORMANCE	Distribution	Parking Garage, Canopy distributions available			
	Input Power (W)	20	30	40	53
	Lumens Delivered Parking Distribution (lm)	2278	3329	4713	6347
	Lumens Delivered Canopy Distribution (lm)	2374	3431	4935	6539
	Efficacy (lm/W)	120 - 125	115 - 118	119 - 124	123 - 127
	Color Temperature	5000K, 4000K available			
	CRI	≥70			
	Lumen Maintenance (L70, TM-21 @ 25° C)	≥100,000			
ELECTRICAL	Input Voltage	120-277V			
	Power Factor	≥0.90			
PHYSICAL	Operating Temperature	-40°F - 104°F / -40°C - 40°C			
	Housing	Die-cast Aluminium			
	Lens	Polycarbonate Lens			
QUALIFICATION	Qualifications	DLC 4.2 Premium, cULus (30W, 40W, 58W), ETL (20W), Supports Title 24 Compliance			
	Environment	Outdoor, wet location			
	Warranty	10-year standard warranty*			

ORDERING*:

MODEL	ORDER CODE	NOMINAL WATTAGE	EQUIVALENCY	DISTRIBUTION	FINISH	INPUT VOLTAGE	COLOR TEMPERATURE (CCT)
CPL20AUC50B	1408347	20W	100W MH	Canopy	Bronze	120-277V	5000K
CPL20AUP50B	1408349	20W	100W MH	Parking Garage			
CPL30AUC50B	102005	30W	150W MH	Canopy			
CPL30AUP50B	102001	30W	150W MH	Parking Garage			
CPL40AUC50B	102010	40W	175W MH	Canopy			
CPL40AUP50B	101024	40W	175W MH	Parking Garage			
CPL58AUC50B	102339	53W	250W MH	Canopy			
CPL58AUP50B	102335	53W	250W MH	Parking Garage			

Lighting layouts and spacing criteria available upon request.

*Please contact your MaxLite representative to order products that don't have order codes listed here.