

6S6 CANDELABRA SCREW BASE CLUSTER LEDs

ORDERING INFORMATION: CSB123 5 WC 1 - 24V/25 - DP
 (A) (B) (C) (D) (E) (F)

(A) MODEL
 CSB123
 CSB144
 CSB188

(B) NUMBER OF LEDs
 5 = 5, T1-3/4 CLUSTER LED
 7 = 7, T1-3/4 CLUSTER LED

(C) LED LENS COLOR
 WC = WATER CLEAR

(D) LED EMITTING COLOR & WAVELENGTH
 1 = ULTRA RED (660nm)
 2 = STD. RED (630-635nm)
 U2 = ULTRA HI EFF. RED (623-630nm)
 3 = STD. ORANGE (605-610nm)
 U3 = ULTRA ORANGE (612-620nm)
 4 = STD. YELLOW (585nm)
 U4 = ULTRA YELLOW (590-595nm)
 5 = STD. GREEN (565-570nm)
 *6NW = ULTRA PURE GREEN (520-530nm)
 *8NW = FLUORESCENT "WHITE" (NO nm VALUE)
 *10NW = ULTRA BLUE (465-475nm)
 *11NW = BLUISH GREEN (498-508nm)
 *12NW = SOFT WHITE (NO nm VALUE)
 *Max. Continuous current 10mA.

(E) STANDARD DC & AC OPERATING VOLTAGES/ma
 5 CLUSTER: 18V/25, 24V/25, 28V/25, 36V/15, 48V/12, 60V/15 & 120V/10
 7 CLUSTER: 5V/75, 6V/75, 12V/50, 14V/50, 18V/25, 24V/25, 28V/25, 36V/25, 48V/12, 60V/15 & 120V/10
Note: Please call factory for other voltages.

(F) CENTER CONTACT POLARITY
 DP = DUAL POLARITY

DIRECT INCANDESCENT LAMP REPLACEMENTS
 3S6 & 6S6, ETC...

SING MAT'L. UL94VO APPROVED
 SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

