

Part Type : **LED driver**

Description : **38W-900mA Constant Current**
32W-750mA Constant Current
25W-600mA Constant Current
0-10V Dimmable

Part Number : **ELD50-CX900-V42-UNV-D/S(900/750/600)**

1. Input Requirement

1.1 Input Voltage

The nominal input voltage is 120-277VAC
Operating Range: 108-305VAC

1.2 Frequency

The nominal input frequency is 50Hz/60Hz

1.3 Current

The maximum input current is 0.39 Amp at 120Vac at max output load of 900mA.

1.4 Efficiency

The typical efficiency (watts out / watts in) is 84% @120V
and 86% @277 max output load.

1.5 Power Factor

@ 277VAC, >0.90
@ 120VAC, >0.99

1.6 Inrush Current

120VAC @ 25 DEG C: <50Amp peak

1.7 THD

THD: < 20% @ 25oC 108-305VAC, full load (w/o Dimmer)

2. Output Requirements

2.1 Output Current Setting

Set nominal current at this voltage.

Output	Voltage	Current	Tolerance
38W	Max 42VDC	900mA	+/- 5%
32W	Max 42VDC	750mA	+/- 5%
25W	Max 42VDC	600mA	+/- 5%

2.2 Output Voltage Range

Driver must work at these voltages.

Output	Voltage	Current	Tolerance
38W	26-42DC	900mA	+/- 5%
32W	26-42DC	750mA	+/- 5%
25W	26-42DC	600mA	+/- 5%

2.3 Output Line Regulation

With output clamped to below set points, vary input from 108-305VAC.

Output	Voltage Set Point	Current range
38W	42VDC	855-945mA
32W	42VDC	712-788mA
25W	42VDC	570-630mA

2.4 Current Stability

+/- 3% maximum after 8 hours

2.5 No Load Voltage

Not to exceed 60VDC.

2.6 Ripple Factor

Measured at max rated load and electronic load connecting to the output is see as below : $V_d=42V$ $R_d=0.1$

Ripple factor < 5% ($I_{pk-pk}/2/I_{mean}$).

2.7 Turn on Delay

Measured @ 108-305VAC max rated load: <1 seconds.

3. Protection Requirement

3.1 Short circuit protection:

When operating under any line condition into a short circuit condition for an indefinite period of time, the power supply shall be self recovering when fault condition is removed.

3.2 Over-current protection:

When operating under any line condition into any over load condition for an indefinite period of time, the power supply shall be self recovering when fault condition is removed.

4. Environmental Conditions

4.1 Operating

The power supply shall be capable of operating continuously in any mode without performance deterioration in the following environmental conditions:

4.11 Ambient Temperature:

-20 to 55 Deg C. 100% rated power at 55 Deg C.

4.12 Class P

4.13 Relative Humidity:

5 to 95%, non-condensing

4.14 Cooling:

Convection

4.2 Non-Operating

The power supply shall be capable of standing the following environmental conditions extended periods of time, without sustaining electrical or mechanical damage and subsequent operational deficiencies.

4.2.1 Ambient Temperature:

-40 to 85 Deg C.

4.3 Shock & Vibration:

MIL-STD-810G Shock Method 516.6 procedure IV and Vibration Method 514.6 Procedure I, Category 4

5. Reliability

5.1 MTBF

>300,000hrs calculated to MIL-HDBK217F @ 25 DEG C. rated load.
Ground Benign.

5.2 Product Life

>50000hrs @ Tc= 90 Deg C, rated load.

6. EMC

6.1 Conducted:

FCC Part 15 Class B

6.2 Audible Noise:

Class A sound rating not to exceed 24dBA (audible) when installed in fixture and such fixture is installed in its normal use. The measurement is to be made from a distance not less than 3 feet.

6.3 ESD:

IEC 61000-4-2 Level 2: 4KV Air and Contact.

6.4 Input Transient Protection

Power supply shall comply with IEEE C.62.41-1991, Class A operation. The line transient shall consist of seven strikes of a 100 kHz ring wave, 2.5 kV level for both common mode and differential mode.

7. Safety

7.1 Agency Approvals

UL 8750-LED equipment for use in lighting product
UL1310-CLASS 2 Power units
CSA C22.2 No. 250.13-12-LED equipment for lighting applications

8. Dimmable

8.1 0-10V Dimming

0-10V Input Signal: 0.6-10V
Dimming Range:4-100%

9. Mechanical

9.1 Materials

Metal case

All material to be ROHs compliant to Directive 2002/95/EC

Wires to be Stranded with UL approval

Input: Black & White : 500mm , 18AWG 105°C 600V Solid Line

Output: Red & Blue&White : 800mm , 20AWG 105°C 600V Solid Line

Dimming: Purple & Gray:800mm , 18AWG 105°C 600V Solid Line

