



T5 Preheat

F13T5/CW PH 25PK


Philips T5 Fluorescent Lamps are incredibly powerful, environmentally responsible, long life lamps with an ultra-slim profile. This translates into reduced maintenance and disposal costs and also allows the use of smaller fixtures—which reduces ceiling clutter.

Product data

General Information		Lamp Current (Nom)	
Cap-Base	G5 [G5]		0.170 A
Life To 10% Failures (Nom)	4000 h	Voltage (Nom)	90 V
Life To 50% Failures (Nom)	8000 h	Controls and Dimming	
Life To 50% Failures Preheat (Nom)	8000 h	Dimmable	Yes
System Description	na [-]	Approval and Application	
Light Technical		Energy Efficiency Label (EEL)	A
Color Code	33-640	Mercury (Hg) Content (Nom)	4.4 mg
Initial lumen (Nom)	930 lm	Energy Consumption kWh/1000 h	14 kWh
Color Designation	Cool White (CW)	Product Data	
Lumen Maintenance 10000 h (Nom)	58 %	Order product name	F13T5/CW PH 25PK
Lumen Maintenance 2000 h (Nom)	85 %	EAN/UPC - Product	046677115142
Lumen Maintenance 5000 h (Nom)	70 %	Order code	332536
Chromaticity Coordinate X (Nom)	377	Numerator - Quantity Per Pack	1
Chromaticity Coordinate Y (Nom)	381	Numerator - Packs per outer box	25
Correlated Color Temperature (Nom)	4100 K	Material Nr. (12NC)	928001503332
Luminous Efficacy (rated) (Nom)	71 lm/W	Net Weight (Piece)	40.200 g
Color Rendering Index (Nom)	60	ILCOS Code	FD-13/41/2B-E-G5
Operating and Electrical			
Power (Rated) (Nom)	13.0 W		

T5 Preheat



Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
F13T5/CW PH 25PK	16 mm	516.9 mm	524.0 mm	521.6 mm	531.1 mm

TL Mini 13W/33-640

Photometric data



Lightcolor /33-640

Lightcolor /33-640

