



**Product Number:** 23116

**Order Abbreviation:** F30T8CW

**General Description:** 30W, T8 preheat fluorescent lamp, Cool White phosphor, 4200K color temperature, 60 CRI. 7500 Avg rated life at 3 hrs/start

**\* Full Case Required**

### Product Information

Abbrev. With Packaging Info.	F30T8CW 24/CS 1/SKU
Actual Length (in)	35.78
Actual Length (mm)	908.81
Average Rated Life (hr)	7500
Base	Medium Bipin
Bulb	T8
Color Rendering Index (CRI)	60
Color Temperature/CCT (K)	4200
Diameter (in)	1.09 in
Diameter (mm)	27.80 mm
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	2180
Mean Lumens at 25C	1897
Nominal Length (in)	36 in
Nominal Length (mm)	914.4
Nominal Wattage (W)	30.00

### Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Preheat lamp, starter required.
- Mean lumens are measured at 40% of average rated lamp life.
- The distance between any parts of the lamp and any conductive surface of the luminaire should not be less than 3 mm (applies to all high frequency ballasted systems).
- The lamp should not be in contact with any surface of the luminaire (applies to either high frequency or 60Hz ballasted systems).