

**Presented By:** Candela Corporation  
Contact Phone: (800) 922-9226  
Contact E-mail: sales@candelacorp.com


Customer Name:  
Project Name:  
Fixture Type:



GE  
Lighting

### 16954 - F40/30BX/SPX41

GE Biax® T5 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse



#### CAUTIONS & WARNINGS

##### Caution

- Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

#### NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life
- Life ratings based on rapid start operation. On instant start ballast, life rating is 25% lower.

#### GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T5
Base	4-Pin (2G11)
Wattage	40
Voltage	126
Rated Life	20000 hrs
Starting Temperature	10 °C (50 °F)
LEED-EB MR Credit	176 picograms Hg per mean lumen hour
Primary Application	Facilities;Retail Display;Hospitality;Office;Restaurant;Warehouse

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens	3150
Mean Lumens	2840
Nominal Initial Lumens per Watt	78
Color Temperature	4100 K
Color Rendering Index (CRI)	82

#### ELECTRICAL CHARACTERISTICS

Lamp Current	0.32 A
Current Crest Factor	1.7

#### DIMENSIONS

Maximum Overall Length (MOL)	22.5000 in(571.5 mm)
Nominal Length	22.500 in(571.5 mm)

#### PRODUCT INFORMATION

Product Code	16954
Description	F40/30BX/SPX41
ANSI Code	60901-IEC-6240-2
Standard Package	Master
Standard Package GTIN	10043168169544
Standard Package Quantity	40
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	40
UPC	043168169547