



Product Number: 24823

Order Abbreviation: F48T12/CW/SS

General Description: 32W, 48" MOL, T12 instant start Slimline SUPER SAVER fluorescent lamp, Cool White phosphor, 4200K color temperature, 60 CRI

Product Information

| | |
|------------------------------|------------------------|
| Abbrev. With Packaging Info. | F48T12CWSS 30/CS 1/SKU |
| Actual Length (in) | 46.000 |
| Actual Length (mm) | 1168.40 |
| Average Rated Life (hr) | 9000 |
| Base | Single Pin |
| Bulb | T12 |
| Color Rendering Index (CRI) | 60 |
| Color Temperature/CCT (K) | 4200 |
| Diameter (in) | 1.593 |
| Diameter (mm) | 40.46 |
| Family Brand Name | SuperSaver® |
| Industry Standards | ANSI C78.81 - 2001 |
| Initial Lumens at 25C | 2450 |
| Mean Lumens at 25C | 2200 |
| Mean Lumens at 35C | 2200 |
| Nominal Length (in) | 48.000 |
| Nominal Length (mm) | 1219.20 |
| Nominal Wattage (W) | 32.00 |

Footnotes

- Recommended for use on one or two lamp high power factor, lead, instant-start, indoor ballasts that meet ANSI standards. Not intended for use: (1) at lamp ambient temperatures below 60 degrees F or in drafty locations, (2) on low power factor ballasts, (3) reduced current/reduced light output ballasts, (4) dimming ballasts, or (5) on inverter operated emergency lighting systems unless any of the above equipment is specifically listed for use with 32 watt or 60 watt lamps.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.