

LINEAR AND CIRCULAR FLUORESCENT LAMPS

TRIPHOSPHOR T5

Ø 26mm. - G13 cap

Watts	Bulb	Base	Product Code	Order Code	Pkg	CRI	Lumens	Life (HRS)	Kelvin	MOL
14	T-5	Bi-Pin	1486FH	F14T5/860	20	85	1300	16,000	6000°	24"
14	T-5	Bi-Pin	1484FH	F14T5/840	20	85	1350	16,000	4100°	24"
14	T-5	Bi-Pin	1483FH	F14T5/830	20	85	1350	16,000	3000°	24"
21	T-5	Bi-Pin	2186FH	F21T5/860	20	85	2000	16,000	6000°	36"
21	T-5	Bi-Pin	2184FH	F21T5/840	20	85	2100	16,000	4100°	36"
21	T-5	Bi-Pin	2183FH	F21T5/830	20	85	2100	16,000	3000°	36"
28	T-5	Bi-Pin	2886FH	F28T5/860	20	85	2750	16,000	6000°	48"
28	T-5	Bi-Pin	2484FH	F28T5/840	20	85	5900	16,000	4100°	48"
28	T-5	Bi-Pin	2883FH	F28T5/830	20	85	5900	16,000	3000°	48"
35	T-5	Bi-Pin	3586FH	F35T5/860	20	85	3500	16,000	6000°	58"
35	T-5	Bi-Pin	3584FH	F35T5/840	20	85	3650	16,000	4100°	58"
35	T-5	Bi-Pin	3583FH	F35T5/830	20	85	3650	16,000	3000°	58"

TRIPHOSPHOR T5 - HIGH OUTPUT

Ø 26mm. - G13 cap

Watts	Bulb	Base	Product Code	Order Code	Pkg	CRI	Lumens	Life (HRS)	Kelvin	MOL
24	T-5/HO	Bi-Pin	2486FQ	F24T5HO/860	20	85	1800	16,000	6000°	24"
24	T-5/HO	Bi-Pin	2484FQ	F24T5HO/840	20	85	2000	16,000	4100°	24"
24	T-5/HO	Bi-Pin	2483FQ	F24T5HO/830	20	85	2000	16,000	3000°	24"
39	T-5/HO	Bi-Pin	3986FQ	F39T5HO/860	20	85	3325	16,000	6000°	36"
39	T-5/HO	Bi-Pin	3984FQ	F39T5HO/840	20	85	3500	16,000	4100°	36"
39	T-5/HO	Bi-Pin	3983FQ	F39T5HO/830	20	85	3500	16,000	3000°	36"
54	T-5/HO	Bi-Pin	5486FQ	F54T5HO/860	20	85	4750	16,000	6000°	48"
54	T-5/HO	Bi-Pin	5484FQ	F54T5HO/840	20	85	5000	16,000	4100°	48"
54	T-5/HO	Bi-Pin	5483FQ	F54T5HO/830	20	85	5000	16,000	3000°	48"

STANDARD T8

Ø 26mm. - G13 cap

Watts	Bulb	Base	Product Code	Order Code	Pkg	CRI	Lumens	Life (HRS)	Kelvin	MOL
17	T-8	Bi-Pin	1750L	F17T8/750	30	78	1300	20,000	5000°	24"
17	T-8	Bi-Pin	1733L	F17T8/741	30	78	1300	20,000	4100°	24"
17	T-8	Bi-Pin	1735L	F17T8/735	30	78	1300	20,000	3500°	24"
17	T-8	Bi-Pin	1729L	F17T8/730	30	78	1300	20,000	3000°	24"
25	T-8	Bi-Pin	2550L	F25T8/750	30	78	2100	20,000	5000°	36"
25	T-8	Bi-Pin	2533L	F25T8/741	30	78	2100	20,000	4100°	36"
25	T-8	Bi-Pin	2535L	F25T8/735	30	78	2100	20,000	3500°	36"
25	T-8	Bi-Pin	2529L	F25T8/730	30	78	2100	20,000	3000°	36"
32	T-8	Bi-Pin	3250L	F32T8/750	30	78	3000	20,000	5000°	48"
32	T-8	Bi-Pin	3233L	F32T8/741	30	78	3000	20,000	4100°	48"
32	T-8	Bi-Pin	3235L	F32T8/735	30	78	3000	20,000	3500°	48"
32	T-8	Bi-Pin	3229L	F32T8/730	30	78	3000	20,000	3000°	48"

TRIPHOSPHOR T8

Ø 26mm. - G13 cap

Watts	Bulb	Base	Product Code	Order Code	Pkg	CRI	Lumens	Life (HRS)	Kelvin	MOL
17	T-8	Bi-Pin	1785T	F17T8/850	30	85	1350	20,000	5000°	24"
17	T-8	Bi-Pin	1784T	F17T8/841	30	85	1350	20,000	4100°	24"
17	T-8	Bi-Pin	1735T	F17T8/835	30	85	1350	20,000	3500°	24"
17	T-8	Bi-Pin	1783T	F17T8/830	30	85	1350	20,000	3000°	24"
25	T-8	Bi-Pin	2585T	F25T8/850	30	85	2150	20,000	5000°	36"
25	T-8	Bi-Pin	2584T	F25T8/841	30	85	2150	20,000	3500°	36"
25	T-8	Bi-Pin	2535T	F25T8/835	30	85	2150	20,000	4100°	36"
25	T-8	Bi-Pin	2583T	F25T8/830	30	85	2150	20,000	3000°	36"
32	T-8	Bi-Pin	3285T	F32T8/850	30	85	3350	20,000	5000°	48"
32	T-8	Bi-Pin	3284T	F32T8/841	30	85	3350	20,000	4100°	48"
32	T-8	Bi-Pin	3235T	F32T8/835	30	85	3350	20,000	3500°	48"
32	T-8	Bi-Pin	3283T	F32T8/830	30	85	3350	20,000	3000°	48"