

Presented By: Candela Corporation

Contact Phone: 800-922-9226

Contact E-mail: sales@candelacorp.com

Customer Name:

Project Name:

Fixture Type:



GE
Lighting

31952 - GE Biax® T5 - Facilities; Retail Display; Hospitality; Office;
Restaurant; Warehouse

F55BX/835

Product Photo



GENERAL CHARACTERISTICS

Base Type	Pin/Plug-In
Mercury Content	3 mg
Rated Life Hours-nominal	20000h
Starting Temp (MN)C-degrees	10 °C
Base Description	4-Pin
Mercury-Picogram per mean lm hr	36.8
Primary Application	Facilities Retail Display Hospitality Office Restaurant Warehouse
Product Technology	Compact Fluorescent
Base	2G11
Bulb Shape	T4

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	4080lm
Nominal Initial Lumen per Watt	87
Initial Lumens-nominal	4800lm
Color Rendering Index-CRI	82
Color Temperature	3500K

PRODUCT INFORMATION

Product Code	31952
Description	F55BX/835
Alternative Unit Of Measure	Case
Standard Package Quantity	25
Ean UPC	043168319522
Standard Package GTIN	10043168319529
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	25
Sales Unit	Unit
UCC	043168319522

DIMENSIONS

Nominal Length	20.7 in
Bulb Max Overall Length-MOL	20.7 in

ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts	200W
Rated power (Watts)	55W

CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

NOTES

4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10C). Ballasts are also available that provide reliable starting to 0degrees F (-18C) and -20F (-29C)