

Presented By: Candela Corporation
Contact Phone: (800) 922-9226
Contact E-mail: sales@candelacorp.com




Customer Name:
Project Name:
Fixture Type:



GE
Lighting

31953 - F55BX/840

GE Biax® T5 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Remove and install by grasping only plastic portion of the lamp.

NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life
- Life ratings for the F18BX preheat lamps are based on operating the lamp at 3 hrs per start on a preheat type circuit. Operation on rapid start and instant start ballasts is not recommended. Life ratings for all lamps are based on operating the lamp at 3

GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T5
Base	4-Pin (2G11)
Wattage	55
Voltage	120/101
Rated Life	10000 hrs
Starting Temperature	10 °C (50 °F)
LEED-EB MR Credit	98 picograms Hg per mean lumen hour
Primary Application	Facilities;Retail Display;Hospitality;Office;Restaurant;W

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	4800
Mean Lumens	4080
Nominal Initial Lumens per Watt	87
Color Temperature	4100 K
Color Rendering Index (CRI)	82

ELECTRICAL CHARACTERISTICS

Lamp Current	0.55 A
Current Crest Factor	1.7

DIMENSIONS

Maximum Overall Length (MOL)	20.7000 in(525.8 mm)
Nominal Length	20.700 in(525.8 mm)

PRODUCT INFORMATION

Product Code	31953
Description	F55BX/840
ANSI Code	60901-IEC-6255-2
Standard Package	Case
Standard Package GTIN	10043168319536
Standard Package Quantity	25
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	25
UPC	043168319539