



# LED Filament High CRI Standard Lamps

## Product Specifications



TCP's LED Filament High CRI Standard Lamps combine the beauty and style of traditional lamps, superior energy savings, and the visual of aesthetics of exposed filaments. Exclusive technology provides unmatched longevity and perfect 5-100% dimming. High CRI output provides outstanding color consistency and beautiful natural color rendering.

## Reasons to choose the LED Filament High CRI Standard Lamps from TCP

- High CRI value provides excellent color rendering results and color consistency while maintaining uniformity
- Smooth, Uniform Dimming from 5 – 100%
- Uses up to 85% less energy than halogen & incandescent lamps
- UL approved for damp and enclosed fixtures
- 15,000 hours rated life and low heat generation, which reduces replacement and maintenance costs
- Unique filament LED configuration provides uniform color output
- ANSI construction compliant means lamps fit most general applications

## Ideal Applications

- Table Lamps
- Floor Lamps
- Sconces
- Ceiling Fixtures
- Chandeliers
- Recessed Lighting

## Item Number Key

1 2 3 4 5 6 7 8 9  
F | A19 | D | 40 | 27 | E26 | S | CL | 95

- 1. Lamp Type: Filaments - (F)
- 2. Lamp Shape - (A19, ST19, T06, T10)
- 3. Dimming/Non Dimming - (D, N)
- 4. Incand. Wattage - (25, 40, 60)
- 5. Color Temp. - (27, 30, 40, 50)
- 6. Base - (E12, E26)
- 7. Filament Type - (S)
- 8. Glass Finish, Clear or Frost - (CL, FR)
- 9. CRI - (95)

## Specifications:

Color Temperatures.....2700K, 3000K, 4000K, 5000K  
Input Line Voltage ..... 120 VAC Input Line  
Frequency ..... 50/60HZ  
Lamp Life (Rated) ..... 15,000 hours  
Minimum Starting Temp ..... -30°C

Maximum Operating Temp.....40°C  
CRI..... 95  
Base..... E12 & E26  
Warranty..... 3 Years

## Specifications:



40W FA19 CLEAR



40W FA19 FROST



60W FA19 CLEAR



60W FA19 FROST

| ITEM #                              | DESCRIPTION                 | WATTS | LUMENS | BASE | CCT   | CRI | WATT EQUIV. | LIFE  | FINISH | MOL | DIA. |
|-------------------------------------|-----------------------------|-------|--------|------|-------|-----|-------------|-------|--------|-----|------|
| <b>FA19 40W, E26 Base, Dimmable</b> |                             |       |        |      |       |     |             |       |        |     |      |
| FA19D4027E26SCL95                   | A19 40W 27K E26 CLEAR 95CRI | 4.5   | 450    | E26  | 2700K | 92  | 40          | 15000 | CLEAR  | 4.2 | 3.4  |
| FA19D4027E26SFR95                   | A19 40W 27K E26 FROST 95CRI | 4.5   | 450    | E26  | 2700K | 95  | 40          | 15000 | FROST  | 4.2 | 3.4  |
| FA19D4030E26SCL95                   | A19 40W 30K E26 CLEAR 95CRI | 4.5   | 450    | E26  | 3000K | 95  | 40          | 15000 | CLEAR  | 4.2 | 3.4  |
| FA19D4030E26SFR95                   | A19 40W 30K E26 FROST 95CRI | 4.5   | 450    | E26  | 3000K | 95  | 40          | 15000 | FROST  | 4.2 | 3.4  |
| FA19D4040E26SCL95                   | A19 40W 40K E26 CLEAR 95CRI | 4.5   | 450    | E26  | 4000K | 95  | 40          | 15000 | CLEAR  | 4.2 | 3.4  |
| FA19D4040E26SFR95                   | A19 40W 40K E26 FROST 95CRI | 4.5   | 450    | E26  | 4000K | 95  | 40          | 15000 | FROST  | 4.2 | 3.4  |
| FA19D4050E26SCL95                   | A19 40W 50K E26 CLEAR 95CRI | 4.5   | 450    | E26  | 5000K | 95  | 40          | 15000 | CLEAR  | 4.2 | 3.4  |
| FA19D4050E26SFR95                   | A19 40W 50K E26 FROST 95CRI | 4.5   | 450    | E26  | 5000K | 95  | 40          | 15000 | FROST  | 4.2 | 3.4  |
| <b>FA19 60W, E26 Base, Dimmable</b> |                             |       |        |      |       |     |             |       |        |     |      |
| FA19D6027E26SCL95                   | A19 60W 27K E26 CLEAR 95CRI | 8.0   | 800    | E26  | 2700K | 92  | 60          | 15000 | CLEAR  | 4.2 | 3.4  |
| FA19D6027E26SFR95                   | A19 60W 27K E26 FROST 95CRI | 8.0   | 800    | E26  | 2700K | 95  | 60          | 15000 | FROST  | 4.2 | 3.4  |
| FA19D6030E26SCL95                   | A19 60W 30K E26 CLEAR 95CRI | 8.0   | 800    | E26  | 3000K | 95  | 60          | 15000 | CLEAR  | 4.2 | 3.4  |
| FA19D6030E26SFR95                   | A19 60W 30K E26 FROST 95CRI | 8.0   | 800    | E26  | 3000K | 95  | 60          | 15000 | FROST  | 4.2 | 3.4  |
| FA19D6040E26SCL95                   | A19 60W 40K E26 CLEAR 95CRI | 8.0   | 800    | E26  | 4000K | 95  | 60          | 15000 | CLEAR  | 4.2 | 3.4  |
| FA19D6040E26SFR95                   | A19 60W 40K E26 FROST 95CRI | 8.0   | 800    | E26  | 4000K | 95  | 60          | 15000 | FROST  | 4.2 | 3.4  |
| FA19D6050E26SCL95                   | A19 60W 50K E26 CLEAR 95CRI | 8.0   | 800    | E26  | 5000K | 95  | 60          | 15000 | CLEAR  | 4.2 | 3.4  |
| FA19D6050E26SFR95                   | A19 60W 50K E26 FROST 95CRI | 8.0   | 800    | E26  | 5000K | 95  | 60          | 15000 | FROST  | 4.2 | 3.4  |

## Specifications:



40W ST19 CLEAR



40W ST19 FROST



25W T06 CLEAR



25W T06 FROST



25W T10 CLEAR



25W T10 FROST

| ITEM #                              | DESCRIPTION                  | WATTS | LUMENS | BASE | CCT   | CRI | WATT EQUIV. | LIFE  | FINISH | MOL | DIA. |
|-------------------------------------|------------------------------|-------|--------|------|-------|-----|-------------|-------|--------|-----|------|
| <b>ST19 40W, E26 Base, Dimmable</b> |                              |       |        |      |       |     |             |       |        |     |      |
| FST19D4027E26SCL95                  | ST19 40W 27K E26 CLEAR 95CRI | 5.0   | 450    | E26  | 2700K | 95  | 40          | 15000 | CLEAR  | 5.4 | 2.5  |
| FST19D4027E26SFR95                  | ST19 40W 27K E26 FROST 95CRI | 5.0   | 450    | E26  | 2700K | 95  | 40          | 15000 | FROST  | 5.4 | 2.5  |
| FST19D4030E26SCL95                  | ST19 40W 30K E26 CLEAR 95CRI | 5.0   | 450    | E26  | 3000K | 95  | 40          | 15000 | CLEAR  | 5.4 | 2.5  |
| FST19D4030E26SFR95                  | ST19 40W 30K E26 FROST 95CRI | 5.0   | 450    | E26  | 3000K | 95  | 40          | 15000 | FROST  | 5.4 | 2.5  |
| FST19D4040E26SCL95                  | ST19 40W 40K E26 CLEAR 95CRI | 5.0   | 450    | E26  | 4000K | 95  | 40          | 15000 | CLEAR  | 5.4 | 2.5  |
| FST19D4040E26SFR95                  | ST19 40W 40K E26 FROST 95CRI | 5.0   | 450    | E26  | 4000K | 95  | 40          | 15000 | FROST  | 5.4 | 2.5  |
| FST19D4050E26SCL95                  | ST19 40W 50K E26 CLEAR 95CRI | 5.0   | 450    | E26  | 5000K | 95  | 40          | 15000 | CLEAR  | 5.4 | 2.5  |
| FST19D4050E26SFR95                  | ST19 40W 50K E26 FROST 95CRI | 5.0   | 450    | E26  | 5000K | 95  | 40          | 15000 | FROST  | 5.4 | 2.5  |
| <b>T06 25W, E26 Base, Dimmable</b>  |                              |       |        |      |       |     |             |       |        |     |      |
| FT0603D2527EE12CL95                 | T06 25W 27K E12 CLEAR 95CRI  | 3.0   | 200    | E12  | 2700K | 95  | 25          | 15000 | CLEAR  | 3.3 | 0.8  |
| FT0603D2527EE12FR95                 | T0 6 25W 27K E12 FROST 95CRI | 3.0   | 200    | E12  | 2700K | 95  | 25          | 15000 | FROST  | 3.3 | 0.8  |
| <b>T10 25W, E26 Base, Dimmable</b>  |                              |       |        |      |       |     |             |       |        |     |      |
| FT1005D2530E26SCL95                 | T10 25W 30K E26 CLEAR 95CRI  | 3.0   | 250    | E26  | 3000K | 95  | 25          | 15000 | CLEAR  | 5.4 | 1.2  |
| FT1005D2530E26SFR95                 | T10 25W 30K E26 FROST 95CRI  | 3.0   | 250    | E26  | 3000K | 95  | 25          | 15000 | FROST  | 5.4 | 1.2  |

# TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcpi.com](http://tcpi.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516