

## FEATURES & SPECIFICATIONS

### INTENDED USE

Provides general illumination in residential applications. Ideal for use in closets, foyers, hallways, corridors, bedrooms, offices, utility work areas, stairways and more. **For commercial applications in which 24/7 use is required, use model FMLSL.**

### CONSTRUCTION

Features a white acrylic diffuser and is available in 15" and 20" sizes. Hidden cam-latches provide easy diffuser removal for installation and maintenance.

### OPTICS

15" units produce 2100 lumens, and 20" units produce 4000 lumens, all at 30,000 hours life.

### ELECTRICAL

Fixture operates at 120 volts, 60 Hz.

15" Standard input = 30 watts, 70 lumens per watt.

20" Standard input = 44 watts, 90 lumens per watt.

Works with most standard incandescent dimmers (see list of suggested dimmers).

### INSTALLATION

All mounting hardware included.

### LISTINGS

cUL Certified to US and Canadian standards and listed suitable for damp locations.

FMLSDL 20" is ENERGY STAR® certified.

### WARRANTY

5-year limited warranty. Complete warranty terms located at: This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. [www.acuitybrands.com/support/warranty/terms-and-conditions](http://www.acuitybrands.com/support/warranty/terms-and-conditions)

**Note:** Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.

Catalog Number
Notes
Type

Decorative Indoor

# Residential LED Low Profile Square

## Flush Mount



HIGH-PERFORMANCE LED



### Specifications

	15"	20"
Diameter:	14.75 (37.5)	20 (5.8)
Depth:	3.38 (8.6)	4 (10.2)
Weight:	1.5 lbs (.7 kg)	5 lbs (2.3 kg)

All dimensions are inches (centimeters) unless otherwise indicated.

### ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

**Example:** FMLSDL 20 35840

Series	Module/CRI	Color temperature
<b>FMLSDL 15</b> <sup>1</sup> 15" Residential LED low profile square flush mount	<b>218</b> >80	<b>40</b> 4000 K
<b>FMLSDL 20</b> 20" Residential LED low profile square flush mount	<b>358</b> >80	

### Notes

1 FMLSDL 15 21840 is not ENERGY STAR® certified.

# Residential LED Low Profile Square Flush Mount

## SUGGESTED DIMMERS

The FMLSDL is designed to operate with most standard Triac Based dimmers and is not compatible with 0-10v dimming systems. The following is a list of dimmers tested and does not imply any guarantee or warranty of compatibility with a particular application. Unlisted dimmers do not imply non-compatibility.

Manufacturer	Part number(s)
Lutron	CT-600P/CT-603P
	DV-600P/DV-603P
	CTCL-153P
	DVCL-153P
	AYCL-153P
	DVELV-300P
Leviton	R50-IPL06
	6615-P
Pass & Seymour	HCL453PTCCCV6