

USHIO

XENON LAMPS

XENOLINE™ SERIES



MINIATURE XENON LAMPS FOR GENERAL LIGHTING

The USHIO Xenoline™ series consists of: Festoon, Rigid Loop and Wedge Base miniature Xenon lamps. All Xenoline™ lamps are low voltage and have an extremely long life making these lamps ideal for track and strip lighting.

Available in: Festoon 3W, 5W, 10W; Rigid Loop 5W, 10W; and Wedge Base ranging from 3W to 18W

BENEFITS


- Long life — up to 20,000 hours average life
- UV protected
- Low pressure
- Less heat
- Dimmable
- Compact tubular design

APPLICATIONS


- Accent Lighting
- Track Lighting
- Strip Lighting
- Landscape Lighting

Distributed by:



Watts (W)	Ushio Ordering Code	Ushio Lamp Description	Volts (V)	Amps (A)	Approx Lumens (lm)	Dimensions		Avg Life (h)
						Dia (A)	MOL (B)	
FESTOON - S8.5/8 BASE								
3	5002235	FST 24V-3W/C/XX	24	.131	30	10	40.0	10000
3	5002234	FST 24V-3W/F/XX	24	.131	30	10	40.0	10000
5	5000765	FST 12V-5W/C/XX	12	.370	50	10	44.0	20000
5	5000886	FST 12V-5W/F/XX	12	.370	50	10	44.0	20000
5	5000766	FST 24V-5W/C/XX	24	.192	50	10	44.0	15000
5	5000755	FST 24V-5W/F/XX	24	.192	50	10	44.0	15000
10	5000850	FST 12V-10W/C/XX	12	.740	120	10	44.0	20000
10	5000891	FST 12V-10W/F/XX	12	.740	120	10	44.0	20000
10	5000851	FST 24V-10W/C/XX	24	.385	120	10	44.0	10000
10	5000756	FST 24V-10W/F/XX	24	.385	120	10	44.0	10000
RIGID LOOP								
5	5000852	XRL 12V-5W/C/XX	12	.417	45	10	43.0	20000
5	5000899	XRL 12V-5W/F/XX	12	.417	45	10	43.0	20000
5	5000854	XRL 24V-5W/C/XX	24	.208	40	10	43.0	20000
5	5000883	XRL 24V-5W/F/XX	24	.208	40	10	43.0	20000
10	5000853	XRL 12V-10W/C/XX	12	.833	100	10	43.0	20000
10	5000901	XRL 12V-10W/F/XX	12	.833	100	10	43.0	20000
10	5000855	XRL 24V-10W/C/XX	24	.417	90	10	43.0	20000
10	5000903	XRL 24V-10W/F/XX	24	.417	90	10	43.0	20000
WEDGE BASE								
3.36	1001417	UWX-10122 15LM	14	.240	15	10.3	26.8	19000
5	1001419	UWX-10124 33LM	13.5	.370	33	10.3	26.8	8000
5	1003155	UWX-1045/BULK, 45LM	13.5	.370	45	10	26.8	2000
5	1003156	UWX-1024S/BULK, 55LM	24	.208	55	10	26.8	2000
5	1001598	UWX-1024S/LL 37.7LM	24	.208	37.7	10.3	26.8	10000
5	1002262	UWX-1024S/LL 37.7 Frosted	24	.208	37.7	10.3	26.8	10000
7.2	1003002	UWX-15 67.9LM	24	.300	67.9	15	37.8	2500
7.2	1003151	UWX-15/BULK	24	.300	67.9	15	37.8	3000
7.2	1003698	UWX-918 82LM	12.8		82	15	37.8	10000
7.5	1002272	UWX-T10XEWB 65.3LM	24	.313	65.3	10.3	26.8	10000
10	1003038	UWX-15 126LM	24	.416	126	15	37.8	2000
10	1003152	UWX-15/BULK, 126LM	24	.416	126	15	37.8	3000
11.5	1001430	UWX-15-1 120LM	12	.960	120	15	37.8	10000
18	1001433	UWX-15-5 250LM	12	1.50	250	15	37.8	10000



Festoon



Rigid Loop



Wedge Base

All dimensions are in millimeters

Form No. S-XE-MINI/R-1212

The specifications on this sheet supercede all previously published specifications and may be subject to change for design and specification improvement without prior notice.

© 2012 USHIO America, Inc. All rights reserved.



Scan with a smartphone to view this product online.