

**Presented By:** iLightDepot/GELightingDepot  
**Contact Phone:** 513-272-0800  
**Contact E-mail:** sales@ilightdepot.com

**Customer Name:**  
**Project Name:**  
**Fixture Type:**





**GE**  
**Lighting**

**71434 - GEC218-MVPS-3W**

GE CFL Multi-Volt ProLine™ Electronic Program / Rapid Start Ballast

- Multi-Voltage technology means a single ballast handles voltage from 108V to 305V
- Programmed starting for extended lamp life
- End-of-Lamp-Life Protection
- Color Coded Poke-In Connectors simplifies wiring
- 3-Way Ballast Kit (-3W) includes mounting plate, lead wires, extraction tool and mounting hardware for side exit, bottom exit or bottom exit with studs mounting



**GENERAL CHARACTERISTICS**

Application	2 or 1- CFQ18W/G24q 120-277V Proline PS 3 Way Kit
Category	Compact Fluorescent
Ballast Type	Electronic - Program / Rapid Start
Starting Method	Programmed start
Lamp Wiring	Series
Line Voltage Regulation (+/-)	10.0 %
Case Temperature (MAX)	70.0 °C
Ballast Factor	Normal
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Enclosure Type	Metal
Additional Info	Auto-restart/Thermally protected/Universal voltage

**PRODUCT INFORMATION**

Product Code	71434
Description	GEC218-MVPS-3W
Standard Package	Master
Standard Package GTIN	10043168714348
Standard Package Quantity	10
Sales Unit	Individual Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168714341

**DIMENSIONS**

<b>Case dimensions</b>	
Length (L)	5.0 in(127.00 mm)
Width (W)	2.4 in(60.96 mm)
Height (H)	1.0 in(25.40 mm)
<b>Mounting dimensions</b>	
Bracket Length (BL)	NaN in(NaN mm)
Mount Length (M)	4.6 in(117.60 mm)
Mount Width (X or F)	NaN in(NaN mm)
Mount Slots (MS)	NaN in(NaN mm)
Weight	1.1 lb
Exit Type	Poke-in
Remote Mounting Distance	20.0 ft
Remote Mounting Wire Gauge	18.0 AWG

**ELECTRICAL CHARACTERISTICS**

Supply Current Frequency	50.0 Hz/60.0 Hz
--------------------------	-----------------

**SAFETY & PERFORMANCE**

- CSA
- UL Class P
- UL Listed
- UL Type 1 Outdoor
- UL Type CC
- UL Type HL
- FCC Part 18 Class B at 120 volts

**SPECIFICATIONS BY LAMP & WATTAGE**

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)(<=)	Crest Factor	THD% (<=)	Min. Starting Temp (°F/°C)
CFTR26W/4P	1	120	28	0.24 A	1.00	3.57	99	1.6	12.0	-20.0 °F / NaN
CFTR26W/4P	1	277	28	0.1 A	1.00	3.57	96	1.6	12.0	-20.0 °F / NaN
CFTR18W/4P	1	120	20	0.17 A	1.05	5.25	97	1.5	10.0	-20.0 °F / NaN
CFTR18W/4P	1	277	20	0.08 A	1.05	5.25	97	1.5	10.0	-20.0 °F / NaN
CFTR18W/4P	2	120	39	0.33 A	1.05	2.69	97	1.5	10.0	-20.0 °F / NaN
CFTR18W/4P	2	277	39	0.14 A	1.05	2.69	97	1.5	10.0	-20.0 °F / NaN

CFS28W/4P	1	120	31	0.26 A	1.00	3.23	99	1.5	10.0	-20.0 °F / NaN
CFS28W/4P	1	277	31	0.11 A	1.00	3.23	97	1.5	10.0	-20.0 °F / NaN
CFS21W/4P	1	120	20	0.16 A	0.90	4.50	97	1.5	15.0	-20.0 °F / NaN
CFS21W/4P	1	277	20	0.07 A	0.90	4.50	97	1.5	15.0	-20.0 °F / NaN
CFS21W/4P	2	120	40	0.33 A	0.91	2.28	99	1.5	10.0	-20.0 °F / NaN
CFS21W/4P	2	277	40	0.14 A	0.91	2.28	99	1.5	10.0	-20.0 °F / NaN
CFS16W/4P	2	120	37	0.31 A	1.00	2.70	99	1.5	10.0	-20.0 °F / NaN
CFS16W/4P	2	277	37	0.13 A	1.00	2.70	99	1.5	10.0	-20.0 °F / NaN
CFQ26W/4P	1	120	28	0.24 A	1.00	3.57	99	1.6	12.0	-20.0 °F / NaN
CFQ26W/4P	1	277	28	0.1 A	1.00	3.57	96	1.6	12.0	-20.0 °F / NaN
CFQ18W/4P	1	120	19	0.07 A	0.95	5.00	99	1.5	10.0	-20.0 °F / NaN
CFQ18W/4P	1	277	19	0.31 A	0.95	5.00	99	1.5	10.0	-20.0 °F / NaN
CFQ18W/4P	2	120	35	0.3 A	1.00	2.86	97	1.5	10.0	-20.0 °F / NaN
CFQ18W/4P	2	277	35	0.13 A	1.00	2.86	97	1.5	10.0	-20.0 °F / NaN

#### WARRANTY INFORMATION

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.