

Outdoor Constant Current Class 1

Programmable Drivers: 277-480V, DALI, 0-10V Combo

PC	SAP#	Description	Max Output (W)	Input Volts	Output Voltage (VDC)	Output Current mA	Max (T) case	Enclosure L x W x H	Enclosure Type	Features
32065	95034075	GED150HCD1P700	150	277-480	100-300	300-720	90c	9.5 x 2.39 x 1.5	Metal Can: Side leads	UL Class1/ Class P 0-10v combo DALI Dimming 6kv/3ka surge
32073	95034076	GED150HCD1P1050	150	277-480	98-215	700-1050	90c	9.5 x 2.39 x 1.5	Metal Can: Side leads	UL Class1/ Class P 0-10v combo DALI Dimming 6kv/3ka surge

Outdoor Constant Current Class 1

Programmable Drivers: 347-480V, 0-10V Dimming

PC	SAP#	Description	Max Output (W)	Input Volts	Output Voltage (VDC)	Output Current mA	Max (T) case	Enclosure L x W x H	Enclosure Type	Features
37036	95014870	D100HP35X70V15M	100	347/480	130-292	300-700	90c	9.5 x 2.39 x 1.5	Metal Can: Side leads	UL Class1 0-10v Dimming to 10% 6kv/3ka surge
42271	35-225097-05	D150HP52X70V15M	150	347-480	110-280	525-700	80c	9.5 x 2.39 x 1.5	Metal Can: Side leads	UL Class1 0-10v Dimming to 10% 6kv/3ka surge
42272	35-225097-06	D150HP751/OV15M	150	347-480	75-190	525-1050	80c	9.5 x 2.39 x 1.5	Metal Can: Side leads	UL Class1 0-10v Dimming to 10% 6kv/3ka surge

