

DC Bayonet Base													
Watts	Volts	Product	Product	Product	Case	Initial Lumens	Average Life Hours	Color Temp. (K)	Filament	M.O.L.		L.C.L.	
(W)	(V)	Code	Description	Comparison	Qty	(lm)				(in.)	(mm)	(in.)	(mm)
50	120	81805	50Q/CL/DC	50Q/CL/DC	50	725	1500	2850	CC-8	2.48	63	1.30	33
	120	82001	50Q/DC	50Q/F/DC	50	690	1500	2850	CC-8	2.48	63	-	-
	130	81854	50Q/CL/DC	50Q/CL/DC/130V	50	725	1500	2850	CC-8	2.48	63	1.30	33
	130	82013	50Q/DC	50Q/F/DC/130V	50	1150	1500	2850	CC-8	2.48	63	-	-
75	28	82148	75Q/CL/DC/28V	75Q/CL/DC/28V	50	1350	2000	2950	CC-8	2.36	60	1.46	37
	120	82099	75Q/CL/DC	75Q/CL/DC	50	1050	1500	2850	CC-8	2.48	63	1.30	33
	120	82246	75Q/DC	75Q/F/DC	50	1150	1500	2850	CC-8	2.48	63	-	-
	130	82081	75Q/CL/DC	75Q/CL/DC/130V	50	1050	1500	2850	CC-8	2.48	63	1.30	33
	130	82253	75Q/DC	75Q/F/DC/130V	50	1150	1500	2850	CC-8	2.48	63	-	-
100	120	80188	100Q/CL/DC	100Q/CL/DC/ESN	50	1600	1500	2850	CC-8	2.48	63	1.30	33
	120	80343	100Q/DC	100Q/F/DC	50	1520	2000	2850	CC-8	2.48	63	-	-
	130	80237	100Q/CL/DC	100Q/CL/DC/130V	50	1600	2000	2850	CC-8	2.48	63	1.30	33
	130	80384	100Q/CD	100Q/F/DC/130V	50	1520	2000	2850	CC-8	2.48	63	-	-
150	120	80482	150Q/CL/DC	150Q/CL/DC/ETC	50	2800	2000	2850	CC-8	2.48	63	1.30	33
	120	80678	150Q/DC	150Q/F/DC/ETF	50	2660	2000	2850	CC-8	2.48	63	-	-
	130	80531	150Q/CL/DC	150Q/CL/DC/130V	50	2800	2000	2850	CC-8	2.48	63	1.30	33
	130	80727	150Q/DC	150Q/F/DC/130V	50	2660	2000	2850	CC-8	2.48	63	-	-
250	120	80874	250Q/CL/DC	250Q/CL/DC/ESS	50	5000	2000	2900	CC-8	2.96	75	1.65	42
	120	81070	250Q/DC	250Q/F/DC/ETB	50	4750	2000	2900	CC-8	2.96	75	-	-
	130	80923	250Q/CL/DC	250Q/CL/130V	50	5000	2000	2900	CC-8	2.96	75	1.65	42
	130	81119	250Q/DC	250Q/F/DC/130V	50	4750	2000	2900	CC-8	2.96	75	-	-
400	120	81266	400Q/CL/DC	400Q/CL/DC	50	8250	2000	2900	CC-8	3.54	90	1.89	48
	120	81364	400Q/DC	400Q/F/DC	50	7840	2000	2900	CC-8	3.54	90	-	-
	130	81275	400Q/CL/DC	400Q/CL/DC/130V	50	8250	2000	2900	CC-8	3.54	90	1.89	48
	130	81370	400Q/DC	400Q/F/DC/130V	50	7840	2000	2900	CC-8	3.54	90	-	-
500	120	81438	500Q/CL/DC	500Q/CL/DC	50	10450	2000	2950	CC-8	3.54	90	1.89	48
	120	81609	500Q/DC	500Q/F/DC	50	9930	2000	2950	CC-8	3.54	90	-	-
	130	81462	500Q/CL/DC	500Q/CL/DC/130V	50	10450	2000	2950	CC-8	3.54	90	1.89	48
	130	81658	500Q/DC	500Q/F/DC/130V	50	9930	2000	2950	CC-8	3.54	90	-	-