

FLUORESCENT SOCKETS

Medium Bi-Pin Butt-On

- A. L395W** (white)
B. L395-2W (white) with two 4-32 trapped holes


660W-600V, (2) 1/8" dia. mounting holes, rapid-start lampholder with 6" leads



Single Pin Slimline

- A. L466** - (660W-1000V)
B. L467 - (660W-600V)


Dim. 2-21/64"Ht. x 1-29/64" W



Snap-In Quickwire Slimline

- A. L516**
B. L517


suggested panel opening 1.520", 660W-600V



Shallow Base Slide On (660W-1000V)

- A. L2537**
B. L2536

designed for 20ga. panel mount



Slide-On Self-Aligning for U-Shape Lamps

- L13180-U** (standard)


660W-600V, 18-20ga. panel mount



Safety Tube Locks white plastic reusable

T199

locks fluorescent Bi-Pin, Tubes in place for added safety and longer tube life



Medium Bi-Pin for U-Shape Lamps

- L13080** (standard)

660W-600V, Dim. 1-1/8" Ht.x 1-3/16" W



Medium Bi-Pin Shunted For Electronic Ballasts

L23351

low profile 18 & 20 ga., 660W-600V



Circline Connector

four leads (black, white, blue, red)

L408

660W-600V



Medium Bi-Pin L3901W

Dim. 1-55/64" Ht x 1-7/16" W, flush or suurface mounting 660W-600V



Medium Bi-Pin

- A. L13351-U** -18 & 20 ga. panel
B. L13051-UN - 20 ga. with nut
C.L13053-UN - 18 ga. with nut

low profile, 660W-600V, Dim. 1-43/64", Ht.x1-11/64" W.



Miniature Bi-Pin for T5 Lamp 75W-250V 10" leads

- A. L420**
B. L420B (bracket)



Medium Bi-Pin Standard

- A. L13357-U** -18 ga. panel
B. L13357-UN - captive nut
C.L13355-U - 20 ga. panel mount


660W-600V, Dim. 2-33/64", Ht.x1-3/8" W. **T8 & T12**



Miniature Bi-Pin Snap-In Quickwire

- A. L13518** - (spring loaded)
B. L13519 - (fixed end)

suggested panel opening 1.520", 660W-600V



Note: 4 Push in Terminals in back for wires ↑