

RECESSED CAN RETROFITS FOR 6" CANS AND LARGER



120-277V
VOLTAGE*

E26
EDISON BASE

UL TYPE B
BALLAST BYPASS
INSTALL METHOD

-4°F to 105°F
OPERATING TEMP

OPEN FIXTURE ONLY

140°
BEAM ANGLE

80+
CRI

L70 50,000
RATED LIFE


5 YEAR WARRANTY

fresh design with silent operation



LED-8054E-G2

- 30W replaces up to 150W BR30 Incandescent
- Appealing design delivers lumens via 140° beam angle.
- Rated for damp locations and open fixtures only.
- Efficient die-cast aluminum heat sink keeps the lamp running cool.
- Fanless - for silent operation.
- Available in 3500, 4000, and 5000K.
- LED-8054-DIM dimmable on 120V.



PART #	UPC	REPLACES	WATTAGE	LUMENS	CCT (K)	BASE
LED-8054E27-G2	844006048815	150W BR30 Incandescent	30W	2500	2700K	E26
LED-8054E35-G2	844006048822	150W BR30 Incandescent	30W	3000	3500K	E26
LED-8054E40-G2	844006048839	150W BR30 Incandescent	30W	3000	4000K	E26
LED-8054E50-G2	844006048846	150W BR30 Incandescent	30W	3000	5000K	E26

DIMMABLE OPTIONS

PART #	UPC	REPLACES	WATTAGE	LUMENS	CCT (K)	BASE
LED-8054E35-G2-DIM	844006068585	150W BR30 Incandescent	30W	3000	3500K	E26
LED-8054E40-G2-DIM	844006068592	150W BR30 Incandescent	30W	3000	4000K	E26
LED-8054E50-G2-DIM	844006068608	150W BR30 Incandescent	30W	3000	5000K	E26

*Dimmable options run on 120V only.

