

RECESSED CAN RETROFITS


FOR 6" CANS AND LARGER



VOLTAGE



EDISON BASE



INSTALL METHOD



OPERATING TEMP



OPEN FIXTURE ONLY



BEAM ANGLE



CRI



RATED LIFE



WARRANTY


fresh design with silent operation



LED-8054E-G2

- 30W replaces up to 150W BR30 Incandescent
- Appealing design delivers lumens via 140° beam angle.
- Rated for damp locations and in open fixtures only.
- Efficient die-cast aluminum heat sink keeps the lamp running cool.
- Fanless - for silent operation.
- Available in 2700, 3500, 4000, and 5000K.

quick and easy energy savings



PART #	UPC	REPLACES	WATTAGE	LUMENS	CCT (K)	BASE
LED-8054E27-G2	844006048815	150W BR30 Incandescent	30W	2500	2700K	E26
LED-8054E35-G2	844006048822	150W BR30 Incandescent	30W	3000	3500K	E26
LED-8054E40-G2	844006048839	150W BR30 Incandescent	30W	3000	4000K	E26
LED-8054E50-G2	844006048846	150W BR30 Incandescent	30W	3000	5000K	E26



Light Efficient Design

LIGHT EFFICIENT DESIGN HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013
INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949
847.380.3540 • led-llc.com

07.01.20 Information is subject to change without notice.